



Living Industrial Partnerships

PRODUCT SPECIFICATION

**ø16mm Stackable
Switches & Indicators**

41
Series





Technical Data.....	1
Specification.....	2
Model Number Structure.....	3 - 8
Indicators.....	9 -10
Non-illuminated pushbutton.....	11 - 12
Illuminated pushbutton.....	13 - 18
illuminated Selector Switch Round	19 - 30
Selector Switch	31
Key Selector Switch.....	32 - 34
Mushroom Head Pushbuttton	35 - 37
Illuminated Mushroom Head Pushbuttton	37 - 42
Dimensions.....	43
Emergency stop.....	44



Stackable Switches & Indicators



WERNER'S 41 Series Switches & Indicators comprise the same most complete line of matching solutions for 16mm bore holes like the 40 Series, but are outfitted with a stackable design. The slim design of all available models will help you to reduce the size of the required panel to a significant extent.

Features Overview

All colors are available as push buttons, indicators, selector switches, key switches as well as push-lock turn/key to reset your switch

Select from illuminated & non-illuminated switches & indicators for your applications

You may choose between both, Multi-Chip as well as filament lamps for illumination

16mm (5/8") shaft diameter makes them very compact and finger friendly

Internal snap action provides unfailing switching and positionin

Highlights

Stackable contacts make them very modular to be used in any application since you can add or remove the contacts according to your individual requirements

Guaranteed highest reliability to be used in connection with high performance solid state, PLC's and other electronic circuit applications

Fitting any application with round, squared and rectangular bezel shapes in many colors

Highly flexible in use to make your needed design changes as easy as possible

41 Series Stackable Switches & Indicators designed and produced by WERNER supply highly reliable mechanisms and the flexibility to change your panel design at any time, without having to think about the smallest detail. And all these extremely useful features come along with a very elegant & stylish design.



Technical Data

Conventional free air thermal current I_{th}

5 A, as per EN IEC 60947-5-1

Switch rating

Switch rating AC with silver contact (gold plated), 250 VAC, 1A, services category AC-15, as per EN IEC 60947-5-1

Short-circuit protection

Series-connected blow-out fuse 5 A gL

Environmental conditions

Switching system

Self cleaning, double-break slow-make element with four-path contacts (contact opening width 2 x 1.5 mm). The slow-make elements are constructed as per EN IEC 60947-5-1.

Electrical characteristics

Conventional free air thermal current I_{th}

5 A, as per EN IEC 60947-5-1

the maximum current in continuous operation and at ambient temperature must not exceed the quoted maximum values.

Switch rating

Switch rating AC (inductive) with silver contact (gold plated), service category AC-13, as per EN IEC 60947-5-1

Switch rating AC (inductive) with silver contact (gold plated), service category AC-14, as per EN IEC 60947-5-1

Switch rating (non-inductive) with silver contact (gold-plated)

Switch rating DC with silver contact (gold plated), service category DC-13, as per EN IEC 60947-5-1

Recommended minimum operational data

Silver contact (Soldering terminal) 5V AC/DC, 1mA

Short-circuit protection

Series-connected blow-out fuse 10 A gL

Overvoltage category

III, as per EN IEC 60947-5-1

Degree of pollution

3, as per EN IEC 60947-1

Contact Ratings (Contact Block)

Rated Insulation Voltage		250V		
Rated Thermal Current		5A		
Operating Voltage (AC/DC)		24V	125V	250V
AC 50/60 Hz	Resistive Load	–	–	5.0A
DC	Resistive Load	1.0 A	0.2A	–
Contact Material		Gold-plated silver		

• Minimum applicable load: 5V AC/DC, 1 mA
(applicable range may vary with operating conditions and load types)

Material

Actuator housing

Polyetherimide (PEI), self-extinguishing

Switching element

Polyamide (PA), Polysulfon (PSU)

Material of contact

Silver (Ag)

Approvals

Approbations and Declaration of conformity

UL	
CE	
RoHS	
CCC	
Demko	

Mechanical characteristics

Terminals

Soldering terminal

max. wire-cross section 2 x 1.0 mm²

max. wire-cross section of stranded cable

1 x 0.75 mm² also pluggable 2.8 x 0.5 mm

Actuating force

max. 65 N (measured on mushroom-head cap)

Unlock torque

15 Ncm

Actuating travel

5.5 mm

Rebound time

2 ms

Weight (approx.)

Shape	Model No.	90° 2 Positions	Model No.	45° 3 Positions
Round	41.61	28.9 to 30.9g	41.71	29.6 to 30.6g
Square	41.62	29.8 to 31.8g	41.72	30.6 to 31.6g
Rectangle	41.63	30.4 to 32.4g	41.73	31.6 to 32.6g




Specifications

Operating Temperature		-20 to +70°C (no freezing)
Storage Temperature		-30 to +80°C
Operating Humidity		45 to 85% RH (no condensation)
Contact Resistance		50 mΩ maximum (initial value)
Insulation Resistance		100 MΩ minimum (500V DC megger)
Dielectric Strength	Switch Unit	Between live and dead metal parts: 2,000V AC, 1 minute Between terminals of different poles: 2,000V AC, 1 minute Between terminals of the same pole: 1,000V AC, 1 minute Between contact and lamp terminals: 1,500V AC, 1 minute
	Illumination Unit	Between live part and ground: 2,000V AC, 1 minute
Vibration Resistance		Operating extremes: 5 to 65 Hz, amplitude 1mm
Shock Resistance		Damage limits: 500 m/sz (50G) Operating extremes: 200 m/sz (20G)
Mechanical Durability (minimum operations)		Momentary: 1,250,000 operations Maintained: 250,000 operations Pushlock Turn Reset: 100,000 operations Selector Switch: 250,000 operations Key Selector Switch: 250,000 operations
Electrical Durability (minimum operations)		Other than Maintained: 1000,000 operations Maintained: 100,000 operations (Switching frequency 1200 operations/h)
Degree of Protection		Enclosed (IP40) Waterproof, dust-tight (IP65)

Key Selector Switch Model Selection


Operator position can be changed by WERNER's original bezel rotating and locking system. The bezel can be locked at every 45° and bezel rotation is prevented while mounting on a panel.



Contact Arrangement

Contact Arrangement

- 1NO-1NC: Middle
- 2NO-2NC: Upper & Lower
- 3NO-3NC: Upper, Middle & Lower





Model Number Structure - Indicators



41.14.04.11.06

Series	
41	Series Switches and Indicators

Operation Type	
1	Indicators

Shape	
4	Round Illuminated
5	Square Illuminated
6	Rectangular Illuminated

Contact	
0	No Contacts

Voltage	
06	6VAC/DC
12	12VAC/DC
24	24VAC/DC

Lamp Type	
1	LED
2	Filament

Protection	
1	IP40
2	IP65

Color	
2	Red
3	Amber
4	Yellow
5	Green
6	Blue
9	White



Model Number Structure - Pushbuttons



41.26.15.11.12

Series	
41 Series Switches and Indicators	

Operation Type	
2	Pushbutton Momentary
3	Pushbutton Maintained

Style	
1	Round Non-Illuminated
2	Square Non-Illuminated
3	Rectangular Non-Illuminated
4	Round Illuminated
5	Square Illuminated
6	Rectangular Illuminated


Contact	
1	1NO-1NC
2	2NO-2NC
3	3NO-3NC

Operating Voltage	
00	No Voltage
06	6V
12	12V
24	24V

Lamp Type	
0	No Lamp
1	LED
2	Filament

Degree of Protection	
1	IP40
2	IP65

Colour	
0	Black*
2	Red
3	Amber
4	Yellow
5	Green
6	Blue
9	White



* Suitable for Non-Illuminated Types.



Model Number Structure - Mushroom Head Pushbuttons



41.84.12.11.12

Series	
41 Series Switches and Indicators	

Operation Type	
8	Mushroom Head Momentary
9	Mushroom Head Maintained

Style	
1	Round Non-Illuminated
2	Square Non-Illuminated
3	Rectangular Non-Illuminated
4	Round Illuminated
5	Square Illuminated
6	Rectangular Illuminated

Contact	
1	1NO-1NC
2	2NO-2NC
3	3NO-3NC

Operating Voltage	
00	No Voltage
06	6V
12	12V
24	24V

Lamp Type	
0	No Lamp
1	LED
2	Filament

Degree of Protection	
1	IP40
2	IP65

Colour	
0	Black*
2	Red
3	Amber
4	Yellow
5	Green
6	Blue
9	White

* Suitable for Non-Illuminated Types.



Model Number Structure - Selector Switch



41.43.10.11

Series	
41 Series Switches and Indicators	

Operation Type	
4	Selector Switch 90°- 2 Positions
5	Selector Switch 45°- 3 Positions

Shape	
1	Round Non-Illuminated
2	Square Non-Illuminated
3	Rectangular Non-Illuminated

Position	
1	Maintained
2	Spring Return From Right
3	Spring Return From Left
4	Spring Return Two Ways

Protection	
1	IP40
2	IP65

Color	
0	Black

Contact	
1	1NO-1NC
2	2NO-2NC
3	3NO-3NC



Model Number Structure - Illuminated Selector Switch



41.46.14.112.12

Series	
41	Series Switches and Indicators

Operation Type	
4	Selector Switch 90°- 2 Positions
5	Selector Switch 45°- 3 Positions

Shape	
4	Round Illuminated
5	Square Illuminated
6	Rectangular Illuminated

Contact	
1	SPDT
2	DPDT

Color	
2	Red
3	Amber
4	Yellow
5	Green
6	Blue
9	White

Voltage	
06	6V AC/DC
12	12V AC/DC
24	24V AC/DC

Lamp Type	
1	LED
2	Filament

Position	
1	Maintained
2	Spring Return From Right
3	Spring Return From Left
4	Spring Return Two Ways

Protection	
1	IP40
2	IP65



Model Number Structure - Key Selector Switches



41.63.10.112

Series	
41 Series Switches and Indicators	

Operation Type	
6	90° 2 Positions
7	45° 3 Positions

Shape	
1	Round
2	Square
3	Rectangular

Contact	
1	1NO-1NC
2	2NO-2NC
3	3NO-3NC

Colour	
0	Black
2	Red
3	Amber
4	Yellow
5	Green
6	Blue
9	White

Key Retained / Removable	
1	Key Removable at all sides
2	Key Retained at Right
3	Key Retained at Left
4	Key Retained at Right & Left
5	Key Retained at Center
6	Key Retained at Center & Right
7	Key Retained at Center & Left


Positions	
1	Maintained
2	Spring Return from Right
3	Spring Return from Left
4	Spring Return two Ways

Degree of Protection	
1	IP40
2	IP65

Indicator

Appearance	Lamp	Voltage	Red		Amber		
			IP40	IP65	IP40	IP65	
 Round	LED	6V	41.14.02.11.06	41.14.02.21.06	41.14.03.11.06	41.14.03.21.06	
		12V	41.14.02.11.12	41.14.02.21.12	41.14.03.11.12	41.14.03.21.12	
		24V	41.14.02.11.24	41.14.02.21.24	41.14.03.11.24	41.14.03.21.24	
	Filament	6V	41.14.02.12.06	41.14.02.22.06	41.14.03.12.06	41.14.03.22.06	
		12V	41.14.02.12.12	41.14.02.22.12	41.14.03.12.12	41.14.03.22.12	
		24V	41.14.02.12.24	41.14.02.22.24	41.14.03.12.24	41.14.03.22.24	
 Square	LED	6V	41.15.02.11.06	41.15.02.21.06	41.15.03.11.06	41.15.03.21.06	
		12V	41.15.02.11.12	41.15.02.21.12	41.15.03.11.12	41.15.03.21.12	
		24V	41.15.02.11.24	41.15.02.21.24	41.15.03.11.24	41.15.03.21.24	
	Filament	6V	41.15.02.12.06	41.15.02.22.06	41.15.03.12.06	41.15.03.22.06	
		12V	41.15.02.12.12	41.15.02.22.12	41.15.03.12.12	41.15.03.22.12	
		24V	41.15.02.12.24	41.15.02.22.24	41.15.03.12.24	41.15.03.22.24	
 Rectangular	LED	6V	41.16.02.11.06	41.16.02.21.06	41.16.03.11.06	41.16.03.21.06	
		12V	41.16.02.11.12	41.16.02.21.12	41.16.03.11.12	41.16.03.21.12	
		24V	41.16.02.11.24	41.16.02.21.24	41.16.03.11.24	41.16.03.21.24	
	Filament	6V	41.16.02.12.06	41.16.02.22.06	41.16.03.12.06	41.16.03.22.06	
		12V	41.16.02.12.12	41.16.02.22.12	41.16.03.12.12	41.16.03.22.12	
		24V	41.16.02.12.24	41.16.02.22.24	41.16.03.12.24	41.16.03.22.24	

Dimensions - Indicator



Indicator

Yellow		Green		Blue		White	
IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
41.14.04.11.06	41.14.04.21.06	41.14.05.11.06	41.14.05.21.06	41.14.06.11.06	41.14.06.21.06	41.14.09.11.06	41.14.09.21.06
41.14.04.11.12	41.14.04.21.12	41.14.05.11.12	41.14.05.21.12	41.14.06.11.12	41.14.06.21.12	41.14.09.11.12	41.14.09.21.12
41.14.04.11.24	41.14.04.21.24	41.14.05.11.24	41.14.05.21.24	41.14.06.11.24	41.14.06.21.24	41.14.09.11.24	41.14.09.21.24
41.14.04.12.06	41.14.04.22.06	41.14.05.12.06	41.14.05.22.06	41.14.06.12.06	41.14.06.22.06	41.14.09.12.06	41.14.09.22.06
41.14.04.12.12	41.14.04.22.12	41.14.05.12.12	41.14.05.22.12	41.14.06.12.12	41.14.06.22.12	41.14.09.12.12	41.14.09.22.12
41.14.04.12.24	41.14.04.22.24	41.14.05.12.24	41.14.05.22.24	41.14.06.12.24	41.14.06.22.24	41.14.09.12.24	41.14.09.22.24
41.15.04.11.06	41.15.04.21.06	41.15.05.11.06	41.15.05.21.06	41.15.06.11.06	41.15.06.21.06	41.15.09.11.06	41.15.09.21.06
41.15.04.11.12	41.15.04.21.12	41.15.05.11.12	41.15.05.21.12	41.15.06.11.12	41.15.06.21.12	41.15.09.11.12	41.15.09.21.12
41.15.04.11.24	41.15.04.21.24	41.15.05.11.24	41.15.05.21.24	41.15.06.11.24	41.15.06.21.24	41.15.09.11.24	41.15.09.21.24
41.15.04.12.06	41.15.04.22.06	41.15.05.12.06	41.15.05.22.06	41.15.06.12.06	41.15.06.22.06	41.15.09.12.06	41.15.09.22.06
41.15.04.12.12	41.15.04.22.12	41.15.05.12.12	41.15.05.22.12	41.15.06.12.12	41.15.06.22.12	41.15.09.12.12	41.15.09.22.12
41.15.04.12.24	41.15.04.22.24	41.15.05.12.24	41.15.05.22.24	41.15.06.12.24	41.15.06.22.24	41.15.09.12.24	41.15.09.22.24
41.16.04.11.06	41.16.04.21.06	41.16.05.11.06	41.16.05.21.06	41.16.06.11.06	41.16.06.21.06	41.16.09.11.06	41.16.09.21.06
41.16.04.11.12	41.16.04.21.12	41.16.05.11.12	41.16.05.21.12	41.16.06.11.12	41.16.06.21.12	41.16.09.11.12	41.16.09.21.12
41.16.04.11.24	41.16.04.21.24	41.16.05.11.24	41.16.05.21.24	41.16.06.11.24	41.16.06.21.24	41.16.09.11.24	41.16.09.21.24
41.16.04.12.06	41.16.04.22.06	41.16.05.12.06	41.16.05.22.06	41.16.06.12.06	41.16.06.22.06	41.16.09.12.06	41.16.09.22.06
41.16.04.12.12	41.16.04.22.12	41.16.05.12.12	41.16.05.22.12	41.16.06.12.12	41.16.06.22.12	41.16.09.12.12	41.16.09.22.12
41.16.04.12.24	41.16.04.22.24	41.16.05.12.24	41.16.05.22.24	41.16.06.12.24	41.16.06.22.24	41.16.09.12.24	41.16.09.22.24

Nomenclature - Indicator




Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Non-Illuminated Pushbutton

Non-Illuminated Pushbutton								
Yellow	Green		Blue		White		Black	
IP65	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
41.21.14.20.00	41.21.15.10.00	41.21.15.20.00	41.21.16.10.00	41.21.16.20.00	41.21.19.10.00	41.21.19.20.00	41.21.10.10.00	41.21.10.20.00
41.21.24.20.00	41.21.25.10.00	41.21.25.20.00	41.21.26.10.00	41.21.26.20.00	41.21.29.10.00	41.21.29.20.00	41.21.20.10.00	41.21.20.20.00
41.21.34.20.00	41.21.35.10.00	41.21.35.20.00	41.21.36.10.00	41.21.36.20.00	41.21.39.10.00	41.21.39.20.00	41.21.30.10.00	41.21.30.20.00
41.24.14.20.00	41.24.15.10.00	41.24.15.20.00	41.24.16.10.00	41.24.16.20.00	41.24.19.10.00	41.24.19.20.00	41.24.10.10.00	41.24.10.20.00
41.24.24.20.00	41.24.25.10.00	41.24.25.20.00	41.24.26.10.00	41.24.26.20.00	41.24.29.10.00	41.24.29.20.00	41.24.20.10.00	41.24.20.20.00
41.24.34.20.00	41.24.35.10.00	41.24.35.20.00	41.24.36.10.00	41.24.36.20.00	41.24.39.10.00	41.24.39.20.00	41.24.30.10.00	41.24.30.20.00
41.31.14.20.00	41.31.15.10.00	41.31.15.20.00	41.31.16.10.00	41.31.16.20.00	41.31.19.10.00	41.31.19.20.00	41.31.10.10.00	41.31.10.20.00
41.31.24.20.00	41.31.25.10.00	41.31.25.20.00	41.31.26.10.00	41.31.26.20.00	41.31.29.10.00	41.31.29.20.00	41.31.20.10.00	41.31.20.20.00
41.31.34.20.00	41.31.35.10.00	41.31.35.20.00	41.31.36.10.00	41.31.36.20.00	41.31.39.10.00	41.31.39.20.00	41.31.30.10.00	41.31.30.20.00
41.34.14.20.00	41.34.15.10.00	41.34.15.20.00	41.34.16.10.00	41.34.16.20.00	41.34.19.10.00	41.34.19.20.00	41.34.10.10.00	41.34.10.20.00
41.34.24.20.00	41.34.25.10.00	41.34.25.20.00	41.34.26.10.00	41.34.26.20.00	41.34.29.10.00	41.34.29.20.00	41.34.20.10.00	41.34.20.20.00
41.34.34.20.00	41.34.35.10.00	41.34.35.20.00	41.34.36.10.00	41.34.36.20.00	41.34.39.10.00	41.34.39.20.00	41.34.30.10.00	41.34.30.20.00
41.22.14.20.00	41.22.15.10.00	41.22.15.20.00	41.22.16.10.00	41.22.16.20.00	41.22.19.10.00	41.22.19.20.00	41.22.10.10.00	41.22.10.20.00
41.22.24.20.00	41.22.25.10.00	41.22.25.20.00	41.22.26.10.00	41.22.26.20.00	41.22.29.10.00	41.22.29.20.00	41.22.20.10.00	41.22.20.20.00
41.22.34.20.00	41.22.35.10.00	41.22.35.20.00	41.22.36.10.00	41.22.36.20.00	41.22.39.10.00	41.22.39.20.00	41.22.30.10.00	41.22.30.20.00
41.25.14.20.00	41.25.15.10.00	41.25.15.20.00	41.25.16.10.00	41.25.16.20.00	41.25.19.10.00	41.25.19.20.00	41.25.10.10.00	41.25.10.20.00
41.25.24.20.00	41.25.25.10.00	41.25.25.20.00	41.25.26.10.00	41.25.26.20.00	41.25.29.10.00	41.25.29.20.00	41.25.20.10.00	41.25.20.20.00
41.25.34.20.00	41.25.35.10.00	41.25.35.20.00	41.25.36.10.00	41.25.36.20.00	41.25.39.10.00	41.25.39.20.00	41.25.30.10.00	41.25.30.20.00
41.32.14.20.00	41.32.15.10.00	41.32.15.20.00	41.32.16.10.00	41.32.16.20.00	41.32.19.10.00	41.32.19.20.00	41.32.10.10.00	41.32.10.20.00
41.32.24.20.00	41.32.25.10.00	41.32.25.20.00	41.32.26.10.00	41.32.26.20.00	41.32.29.10.00	41.32.29.20.00	41.32.20.10.00	41.32.20.20.00
41.32.34.20.00	41.32.35.10.00	41.32.35.20.00	41.32.36.10.00	41.32.36.20.00	41.32.39.10.00	41.32.39.20.00	41.32.30.10.00	41.32.30.20.00
41.35.14.20.00	41.35.15.10.00	41.35.15.20.00	41.35.16.10.00	41.35.16.20.00	41.35.19.10.00	41.35.19.20.00	41.35.10.10.00	41.35.10.20.00
41.35.24.20.00	41.35.25.10.00	41.35.25.20.00	41.35.26.10.00	41.35.26.20.00	41.35.29.10.00	41.35.29.20.00	41.35.20.10.00	41.35.20.20.00
41.35.34.20.00	41.35.35.10.00	41.35.35.20.00	41.35.36.10.00	41.35.36.20.00	41.35.39.10.00	41.35.39.20.00	41.35.30.10.00	41.35.30.20.00
41.23.14.20.00	41.23.15.10.00	41.23.15.20.00	41.23.16.10.00	41.23.16.20.00	41.23.19.10.00	41.23.19.20.00	41.23.10.10.00	41.23.10.20.00
41.23.24.20.00	41.23.25.10.00	41.23.25.20.00	41.23.26.10.00	41.23.26.20.00	41.23.29.10.00	41.23.29.20.00	41.23.20.10.00	41.23.20.20.00
41.23.34.20.00	41.23.35.10.00	41.23.35.20.00	41.23.36.10.00	41.23.36.20.00	41.23.39.10.00	41.23.39.20.00	41.23.30.10.00	41.23.30.20.00
41.26.14.20.00	41.26.15.10.00	41.26.15.20.00	41.26.16.10.00	41.26.16.20.00	41.26.19.10.00	41.26.19.20.00	41.26.10.10.00	41.26.10.20.00
41.26.24.20.00	41.26.25.10.00	41.26.25.20.00	41.26.26.10.00	41.26.26.20.00	41.26.29.10.00	41.26.29.20.00	41.26.20.10.00	41.26.20.20.00
41.26.34.20.00	41.26.35.10.00	41.26.35.20.00	41.26.36.10.00	41.26.36.20.00	41.26.39.10.00	41.26.39.20.00	41.26.30.10.00	41.26.30.20.00
41.33.14.20.00	41.33.15.10.00	41.33.15.20.00	41.33.16.10.00	41.33.16.20.00	41.33.19.10.00	41.33.19.20.00	41.33.10.10.00	41.33.10.20.00
41.33.24.20.00	41.33.25.10.00	41.33.25.20.00	41.33.26.10.00	41.33.26.20.00	41.33.29.10.00	41.33.29.20.00	41.33.20.10.00	41.33.20.20.00
41.33.34.20.00	41.33.35.10.00	41.33.35.20.00	41.33.36.10.00	41.33.36.20.00	41.33.39.10.00	41.33.39.20.00	41.33.30.10.00	41.33.30.20.00
41.36.14.20.00	41.36.15.10.00	41.36.15.20.00	41.36.16.10.00	41.36.16.20.00	41.36.19.10.00	41.36.19.20.00	41.36.10.10.00	41.36.10.20.00
41.36.24.20.00	41.36.25.10.00	41.36.25.20.00	41.36.26.10.00	41.36.26.20.00	41.36.29.10.00	41.36.29.20.00	41.36.20.10.00	41.36.20.20.00
41.36.34.20.00	41.36.35.10.00	41.36.35.20.00	41.36.36.10.00	41.36.36.20.00	41.36.39.10.00	41.36.39.20.00	41.36.30.10.00	41.36.30.20.00

Nomenclature - Non-Illuminated Pushbutton




Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	
0	Black	

Illuminated Pushbutton - Round

Appearance	Operation	Lamp	Voltage	Contact	Red		Amber			
					IP40	IP65	IP40	IP65		
 <p>Round Illuminated</p>	Momentary	LED	6V	1NO-1NC	41.24.12.11.06	41.24.12.21.06	41.24.13.11.06	41.24.13.21.06		
				2NO-2NC	41.24.22.11.06	41.24.22.21.06	41.24.23.11.06	41.24.23.21.06		
				3NO-3NC	41.24.32.11.06	41.24.32.21.06	41.24.33.11.06	41.24.33.21.06		
			12V	1NO-1NC	41.24.12.11.12	41.24.12.21.12	41.24.13.11.12	41.24.13.21.12		
				2NO-2NC	41.24.22.11.12	41.24.22.21.12	41.24.23.11.12	41.24.23.21.12		
				3NO-3NC	41.24.32.11.12	41.24.32.21.12	41.24.33.11.12	41.24.33.21.12		
		24V	1NO-1NC	41.24.12.11.24	41.24.12.21.24	41.24.13.11.24	41.24.13.21.24			
			2NO-2NC	41.24.22.11.24	41.24.22.21.24	41.24.23.11.24	41.24.23.21.24			
			3NO-3NC	41.24.32.11.24	41.24.32.21.24	41.24.33.11.24	41.24.33.21.24			
		Filament	6V	1NO-1NC	41.24.12.12.06	41.24.12.22.06	41.24.13.12.06	41.24.13.22.06		
				2NO-2NC	41.24.22.12.06	41.24.22.22.06	41.24.23.12.06	41.24.23.22.06		
				3NO-3NC	41.24.32.12.06	41.24.32.22.06	41.24.33.12.06	41.24.33.22.06		
	12V		1NO-1NC	41.24.12.12.12	41.24.12.22.12	41.24.13.12.12	41.24.13.22.12			
			2NO-2NC	41.24.22.12.12	41.24.22.22.12	41.24.23.12.12	41.24.23.22.12			
			3NO-3NC	41.24.32.12.12	41.24.32.22.12	41.24.33.12.12	41.24.33.22.12			
	24V	1NO-1NC	41.24.12.12.24	41.24.12.22.24	41.24.13.12.24	41.24.13.22.24				
		2NO-2NC	41.24.22.12.24	41.24.22.22.24	41.24.23.12.24	41.24.23.22.24				
		3NO-3NC	41.24.32.12.24	41.24.32.22.24	41.24.33.12.24	41.24.33.22.24				
	 <p>Round Illuminated</p>	Maintained	LED	6V	1NO-1NC	41.34.12.11.06	41.34.12.21.06	41.34.13.11.06	41.34.13.21.06	
					2NO-2NC	41.34.22.11.06	41.34.22.21.06	41.34.23.11.06	41.34.23.21.06	
					3NO-3NC	41.34.32.11.06	41.34.32.21.06	41.34.33.11.06	41.34.33.21.06	
				12V	1NO-1NC	41.34.12.11.12	41.34.12.21.12	41.34.13.11.12	41.34.13.21.12	
					2NO-2NC	41.34.22.11.12	41.34.22.21.12	41.34.23.11.12	41.34.23.21.12	
					3NO-3NC	41.34.32.11.12	41.34.32.21.12	41.34.33.11.12	41.34.33.21.12	
24V			1NO-1NC	41.34.12.11.24	41.34.12.21.24	41.34.13.11.24	41.34.13.21.24			
			2NO-2NC	41.34.22.11.24	41.34.22.21.24	41.34.23.11.24	41.34.23.21.24			
			3NO-3NC	41.34.32.11.24	41.34.32.21.24	41.34.33.11.24	41.34.33.21.24			
Filament			6V	1NO-1NC	41.34.12.12.06	41.34.12.22.06	41.34.13.12.06	41.34.13.22.06		
				2NO-2NC	41.34.22.12.06	41.34.22.22.06	41.34.23.12.06	41.34.23.22.06		
				3NO-3NC	41.34.32.12.06	41.34.32.22.06	41.34.33.12.06	41.34.33.22.06		
		12V	1NO-1NC	41.34.12.12.12	41.34.12.22.12	41.34.13.12.12	41.34.13.22.12			
			2NO-2NC	41.34.22.12.12	41.34.22.22.12	41.34.23.12.12	41.34.23.22.12			
			3NO-3NC	41.34.32.12.12	41.34.32.22.12	41.34.33.12.12	41.34.33.22.12			
24V		1NO-1NC	41.34.12.12.24	41.34.12.22.24	41.34.13.12.24	41.34.13.22.24				
		2NO-2NC	41.34.22.12.24	41.34.22.22.24	41.34.23.12.24	41.34.23.22.24				
		3NO-3NC	41.34.32.12.24	41.34.32.22.24	41.34.33.12.24	41.34.33.22.24				

Dimensions - Illuminated Pushbutton



Illuminated Pushbutton - Round

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.24.14.11.06	41.24.14.21.06	41.24.15.11.06	41.24.15.21.06	41.24.16.11.06	41.24.16.21.06	41.24.19.11.06	41.24.19.21.06
	41.24.24.11.06	41.24.24.21.06	41.24.25.11.06	41.24.25.21.06	41.24.26.11.06	41.24.26.21.06	41.24.29.11.06	41.24.29.21.06
	41.24.34.11.06	41.24.34.21.06	41.24.35.11.06	41.24.35.21.06	41.24.36.11.06	41.24.36.21.06	41.24.39.11.06	41.24.39.21.06
	41.24.14.11.12	41.24.14.21.12	41.24.15.11.12	41.24.15.21.12	41.24.16.11.12	41.24.16.21.12	41.24.19.11.12	41.24.19.21.12
	41.24.24.11.12	41.24.24.21.12	41.24.25.11.12	41.24.25.21.12	41.24.26.11.12	41.24.26.21.12	41.24.29.11.12	41.24.29.21.12
	41.24.34.11.12	41.24.34.21.12	41.24.35.11.12	41.24.35.21.12	41.24.36.11.12	41.24.36.21.12	41.24.39.11.12	41.24.39.21.12
	41.24.14.11.24	41.24.14.21.24	41.24.15.11.24	41.24.15.21.24	41.24.16.11.24	41.24.16.21.24	41.24.19.11.24	41.24.19.21.24
	41.24.24.11.24	41.24.24.21.24	41.24.25.11.24	41.24.25.21.24	41.24.26.11.24	41.24.26.21.24	41.24.29.11.24	41.24.29.21.24
	41.24.34.11.24	41.24.34.21.24	41.24.35.11.24	41.24.35.21.24	41.24.36.11.24	41.24.36.21.24	41.24.39.11.24	41.24.39.21.24
	41.24.14.12.06	41.24.14.22.06	41.24.15.12.06	41.24.15.22.06	41.24.16.12.06	41.24.16.22.06	41.24.19.12.06	41.24.19.22.06
	41.24.24.12.06	41.24.24.22.06	41.24.25.12.06	41.24.25.22.06	41.24.26.12.06	41.24.26.22.06	41.24.29.12.06	41.24.29.22.06
	41.24.34.12.06	41.24.34.22.06	41.24.35.12.06	41.24.35.22.06	41.24.36.12.06	41.24.36.22.06	41.24.39.12.06	41.24.39.22.06
	41.24.14.12.12	41.24.14.22.12	41.24.15.12.12	41.24.15.22.12	41.24.16.12.12	41.24.16.22.12	41.24.19.12.12	41.24.19.22.12
	41.24.24.12.12	41.24.24.22.12	41.24.25.12.12	41.24.25.22.12	41.24.26.12.12	41.24.26.22.12	41.24.29.12.12	41.24.29.22.12
	41.24.34.12.12	41.24.34.22.12	41.24.35.12.12	41.24.35.22.12	41.24.36.12.12	41.24.36.22.12	41.24.39.12.12	41.24.39.22.12
	41.24.14.12.24	41.24.14.22.24	41.24.15.12.24	41.24.15.22.24	41.24.16.12.24	41.24.16.22.24	41.24.19.12.24	41.24.19.22.24
	41.24.24.12.24	41.24.24.22.24	41.24.25.12.24	41.24.25.22.24	41.24.26.12.24	41.24.26.22.24	41.24.29.12.24	41.24.29.22.24
	41.24.34.12.24	41.24.34.22.24	41.24.35.12.24	41.24.35.22.24	41.24.36.12.24	41.24.36.22.24	41.24.39.12.24	41.24.39.22.24
	41.34.14.11.06	41.34.14.21.06	41.34.15.11.06	41.34.15.21.06	41.34.16.11.06	41.34.16.21.06	41.34.19.11.06	41.34.19.21.06
	41.34.24.11.06	41.34.24.21.06	41.34.25.11.06	41.34.25.21.06	41.34.26.11.06	41.34.26.21.06	41.34.29.11.06	41.34.29.21.06
	41.34.34.11.06	41.34.34.21.06	41.34.35.11.06	41.34.35.21.06	41.34.36.11.06	41.34.36.21.06	41.34.39.11.06	41.34.39.21.06
	41.34.14.11.12	41.34.14.21.12	41.34.15.11.12	41.34.15.21.12	41.34.16.11.12	41.34.16.21.12	41.34.19.11.12	41.34.19.21.12
	41.34.24.11.12	41.34.24.21.12	41.34.25.11.12	41.34.25.21.12	41.34.26.11.12	41.34.26.21.12	41.34.29.11.12	41.34.29.21.12
	41.34.34.11.12	41.34.34.21.12	41.34.35.11.12	41.34.35.21.12	41.34.36.11.12	41.34.36.21.12	41.34.39.11.12	41.34.39.21.12
	41.34.14.11.24	41.34.14.21.24	41.34.15.11.24	41.34.15.21.24	41.34.16.11.24	41.34.16.21.24	41.34.19.11.24	41.34.19.21.24
	41.34.24.11.24	41.34.24.21.24	41.34.25.11.24	41.34.25.21.24	41.34.26.11.24	41.34.26.21.24	41.34.29.11.24	41.34.29.21.24
	41.34.34.11.24	41.34.34.21.24	41.34.35.11.24	41.34.35.21.24	41.34.36.11.24	41.34.36.21.24	41.34.39.11.24	41.34.39.21.24
	41.34.14.12.06	41.34.14.22.06	41.34.15.12.06	41.34.15.22.06	41.34.16.12.06	41.34.16.22.06	41.34.19.12.06	41.34.19.22.06
	41.34.24.12.06	41.34.24.22.06	41.34.25.12.06	41.34.25.22.06	41.34.26.12.06	41.34.26.22.06	41.34.29.12.06	41.34.29.22.06
	41.34.34.12.06	41.34.34.22.06	41.34.35.12.06	41.34.35.22.06	41.34.36.12.06	41.34.36.22.06	41.34.39.12.06	41.34.39.22.06
	41.34.14.12.12	41.34.14.22.12	41.34.15.12.12	41.34.15.22.12	41.34.16.12.12	41.34.16.22.12	41.34.19.12.12	41.34.19.22.12
	41.34.24.12.12	41.34.24.22.12	41.34.25.12.12	41.34.25.22.12	41.34.26.12.12	41.34.26.22.12	41.34.29.12.12	41.34.29.22.12
	41.34.34.12.12	41.34.34.22.12	41.34.35.12.12	41.34.35.22.12	41.34.36.12.12	41.34.36.22.12	41.34.39.12.12	41.34.39.22.12
	41.34.14.12.24	41.34.14.22.24	41.34.15.12.24	41.34.15.22.24	41.34.16.12.24	41.34.16.22.24	41.34.19.12.24	41.34.19.22.24
	41.34.24.12.24	41.34.24.22.24	41.34.25.12.24	41.34.25.22.24	41.34.26.12.24	41.34.26.22.24	41.34.29.12.24	41.34.29.22.24
	41.34.34.12.24	41.34.34.22.24	41.34.35.12.24	41.34.35.22.24	41.34.36.12.24	41.34.36.22.24	41.34.39.12.24	41.34.39.22.24

Nomenclature - Illuminated Pushbutton



41.24.14.21.12

41 Series Switches & Indicators

Operation Type

Shape

Contact

Yellow

Voltage

Lamp type

Protection


Color

Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Illuminated Pushbutton - Square

Appearance	Operation	Lamp	Voltage	Contact	Red		Amber			
					IP40	IP65	IP40	IP65		
 Square Illuminated	Momentary	LED	6V	1NO-1NC	41.25.12.11.06	41.25.12.21.06	41.25.13.11.06	41.25.13.21.06		
				2NO-2NC	41.25.22.11.06	41.25.22.21.06	41.25.23.11.06	41.25.23.21.06		
				3NO-3NC	41.25.32.11.06	41.25.32.21.06	41.25.33.11.06	41.25.33.21.06		
			12V	1NO-1NC	41.25.12.11.12	41.25.12.21.12	41.25.13.11.12	41.25.13.21.12		
				2NO-2NC	41.25.22.11.12	41.25.22.21.12	41.25.23.11.12	41.25.23.21.12		
				3NO-3NC	41.25.32.11.12	41.25.32.21.12	41.25.33.11.12	41.25.33.21.12		
		24V	1NO-1NC	41.25.12.11.24	41.25.12.21.24	41.25.13.11.24	41.25.13.21.24			
			2NO-2NC	41.25.22.11.24	41.25.22.21.24	41.25.23.11.24	41.25.23.21.24			
			3NO-3NC	41.25.32.11.24	41.25.32.21.24	41.25.33.11.24	41.25.33.21.24			
		Filament	6V	1NO-1NC	41.25.12.12.06	41.25.12.22.06	41.25.13.12.06	41.25.13.22.06		
				2NO-2NC	41.25.22.12.06	41.25.22.22.06	41.25.23.12.06	41.25.23.22.06		
				3NO-3NC	41.25.32.12.06	41.25.32.22.06	41.25.33.12.06	41.25.33.22.06		
	12V		1NO-1NC	41.25.12.12.12	41.25.12.22.12	41.25.13.12.12	41.25.13.22.12			
			2NO-2NC	41.25.22.12.12	41.25.22.22.12	41.25.23.12.12	41.25.23.22.12			
			3NO-3NC	41.25.32.12.12	41.25.32.22.12	41.25.33.12.12	41.25.33.22.12			
	24V	1NO-1NC	41.25.12.12.24	41.25.12.22.24	41.25.13.12.24	41.25.13.22.24				
		2NO-2NC	41.25.22.12.24	41.25.22.22.24	41.25.23.12.24	41.25.23.22.24				
		3NO-3NC	41.25.32.12.24	41.25.32.22.24	41.25.33.12.24	41.25.33.22.24				
	 Square Illuminated	Maintained	LED	6V	1NO-1NC	41.35.12.11.06	41.35.12.21.06	41.35.13.11.06	41.35.13.21.06	
					2NO-2NC	41.35.22.11.06	41.35.22.21.06	41.35.23.11.06	41.35.23.21.06	
					3NO-3NC	41.35.32.11.06	41.35.32.21.06	41.35.33.11.06	41.35.33.21.06	
				12V	1NO-1NC	41.35.12.11.12	41.35.12.21.12	41.35.13.11.12	41.35.13.21.12	
					2NO-2NC	41.35.22.11.12	41.35.22.21.12	41.35.23.11.12	41.35.23.21.12	
					3NO-3NC	41.35.32.11.12	41.35.32.21.12	41.35.33.11.12	41.35.33.21.12	
24V			1NO-1NC	41.35.12.11.24	41.35.12.21.24	41.35.13.11.24	41.35.13.21.24			
			2NO-2NC	41.35.22.11.24	41.35.22.21.24	41.35.23.11.24	41.35.23.21.24			
			3NO-3NC	41.35.32.11.24	41.35.32.21.24	41.35.33.11.24	41.35.33.21.24			
Filament			6V	1NO-1NC	41.35.12.12.06	41.35.12.22.06	41.35.13.12.06	41.35.13.22.06		
				2NO-2NC	41.35.22.12.06	41.35.22.22.06	41.35.23.12.06	41.35.23.22.06		
				3NO-3NC	41.35.32.12.06	41.35.32.22.06	41.35.33.12.06	41.35.33.22.06		
		12V	1NO-1NC	41.35.12.12.12	41.35.12.22.12	41.35.13.12.12	41.35.13.22.12			
			2NO-2NC	41.35.22.12.12	41.35.22.22.12	41.35.23.12.12	41.35.23.22.12			
			3NO-3NC	41.35.32.12.12	41.35.32.22.12	41.35.33.12.12	41.35.33.22.12			
24V		1NO-1NC	41.35.12.12.24	41.35.12.22.24	41.35.13.12.24	41.35.13.22.24				
		2NO-2NC	41.35.22.12.24	41.35.22.22.24	41.35.23.12.24	41.35.23.22.24				
		3NO-3NC	41.35.32.12.24	41.35.32.22.24	41.35.33.12.24	41.35.33.22.24				

Dimensions - Illuminated Pushbutton



Illuminated Pushbutton - Square

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.25.14.11.06	41.25.14.21.06	41.25.15.11.06	41.25.15.21.06	41.25.16.11.06	41.25.16.21.06	41.25.19.11.06	41.25.19.21.06
	41.25.24.11.06	41.25.24.21.06	41.25.25.11.06	41.25.25.21.06	41.25.26.11.06	41.25.26.21.06	41.25.29.11.06	41.25.29.21.06
	41.25.34.11.06	41.25.34.21.06	41.25.35.11.06	41.25.35.21.06	41.25.36.11.06	41.25.36.21.06	41.25.39.11.06	41.25.39.21.06
	41.25.14.11.12	41.25.14.21.12	41.25.15.11.12	41.25.15.21.12	41.25.16.11.12	41.25.16.21.12	41.25.19.11.12	41.25.19.21.12
	41.25.24.11.12	41.25.24.21.12	41.25.25.11.12	41.25.25.21.12	41.25.26.11.12	41.25.26.21.12	41.25.29.11.12	41.25.29.21.12
	41.25.34.11.12	41.25.34.21.12	41.25.35.11.12	41.25.35.21.12	41.25.36.11.12	41.25.36.21.12	41.25.39.11.12	41.25.39.21.12
	41.25.14.11.24	41.25.14.21.24	41.25.15.11.24	41.25.15.21.24	41.25.16.11.24	41.25.16.21.24	41.25.19.11.24	41.25.19.21.24
	41.25.24.11.24	41.25.24.21.24	41.25.25.11.24	41.25.25.21.24	41.25.26.11.24	41.25.26.21.24	41.25.29.11.24	41.25.29.21.24
	41.25.34.11.24	41.25.34.21.24	41.25.35.11.24	41.25.35.21.24	41.25.36.11.24	41.25.36.21.24	41.25.39.11.24	41.25.39.21.24
	41.25.14.12.06	41.25.14.22.06	41.25.15.12.06	41.25.15.22.06	41.25.16.12.06	41.25.16.22.06	41.25.19.12.06	41.25.19.22.06
	41.25.24.12.06	41.25.24.22.06	41.25.25.12.06	41.25.25.22.06	41.25.26.12.06	41.25.26.22.06	41.25.29.12.06	41.25.29.22.06
	41.25.34.12.06	41.25.34.22.06	41.25.35.12.06	41.25.35.22.06	41.25.36.12.06	41.25.36.22.06	41.25.39.12.06	41.25.39.22.06
	41.25.14.12.12	41.25.14.22.12	41.25.15.12.12	41.25.15.22.12	41.25.16.12.12	41.25.16.22.12	41.25.19.12.12	41.25.19.22.12
	41.25.24.12.12	41.25.24.22.12	41.25.25.12.12	41.25.25.22.12	41.25.26.12.12	41.25.26.22.12	41.25.29.12.12	41.25.29.22.12
	41.25.34.12.12	41.25.34.22.12	41.25.35.12.12	41.25.35.22.12	41.25.36.12.12	41.25.36.22.12	41.25.39.12.12	41.25.39.22.12
	41.25.14.12.24	41.25.14.22.24	41.25.15.12.24	41.25.15.22.24	41.25.16.12.24	41.25.16.22.24	41.25.19.12.24	41.25.19.22.24
	41.25.24.12.24	41.25.24.22.24	41.25.25.12.24	41.25.25.22.24	41.25.26.12.24	41.25.26.22.24	41.25.29.12.24	41.25.29.22.24
	41.25.34.12.24	41.25.34.22.24	41.25.35.12.24	41.25.35.22.24	41.25.36.12.24	41.25.36.22.24	41.25.39.12.24	41.25.39.22.24
	41.35.14.11.06	41.35.14.21.06	41.35.15.11.06	41.35.15.21.06	41.35.16.11.06	41.35.16.21.06	41.35.19.11.06	41.35.19.21.06
	41.35.24.11.06	41.35.24.21.06	41.35.25.11.06	41.35.25.21.06	41.35.26.11.06	41.35.26.21.06	41.35.29.11.06	41.35.29.21.06
	41.35.34.11.06	41.35.34.21.06	41.35.35.11.06	41.35.35.21.06	41.35.36.11.06	41.35.36.21.06	41.35.39.11.06	41.35.39.21.06
	41.35.14.11.12	41.35.14.21.12	41.35.15.11.12	41.35.15.21.12	41.35.16.11.12	41.35.16.21.12	41.35.19.11.12	41.35.19.21.12
	41.35.24.11.12	41.35.24.21.12	41.35.25.11.12	41.35.25.21.12	41.35.26.11.12	41.35.26.21.12	41.35.29.11.12	41.35.29.21.12
	41.35.34.11.12	41.35.34.21.12	41.35.35.11.12	41.35.35.21.12	41.35.36.11.12	41.35.36.21.12	41.35.39.11.12	41.35.39.21.12
	41.35.14.11.24	41.35.14.21.24	41.35.15.11.24	41.35.15.21.24	41.35.16.11.24	41.35.16.21.24	41.35.19.11.24	41.35.19.21.24
	41.35.24.11.24	41.35.24.21.24	41.35.25.11.24	41.35.25.21.24	41.35.26.11.24	41.35.26.21.24	41.35.29.11.24	41.35.29.21.24
	41.35.34.11.24	41.35.34.21.24	41.35.35.11.24	41.35.35.21.24	41.35.36.11.24	41.35.36.21.24	41.35.39.11.24	41.35.39.21.24
	41.35.14.12.06	41.35.14.22.06	41.35.15.12.06	41.35.15.22.06	41.35.16.12.06	41.35.16.22.06	41.35.19.12.06	41.35.19.22.06
	41.35.24.12.06	41.35.24.22.06	41.35.25.12.06	41.35.25.22.06	41.35.26.12.06	41.35.26.22.06	41.35.29.12.06	41.35.29.22.06
	41.35.34.12.06	41.35.34.22.06	41.35.35.12.06	41.35.35.22.06	41.35.36.12.06	41.35.36.22.06	41.35.39.12.06	41.35.39.22.06
	41.35.14.12.12	41.35.14.22.12	41.35.15.12.12	41.35.15.22.12	41.35.16.12.12	41.35.16.22.12	41.35.19.12.12	41.35.19.22.12
	41.35.24.12.12	41.35.24.22.12	41.35.25.12.12	41.35.25.22.12	41.35.26.12.12	41.35.26.22.12	41.35.29.12.12	41.35.29.22.12
	41.35.34.12.12	41.35.34.22.12	41.35.35.12.12	41.35.35.22.12	41.35.36.12.12	41.35.36.22.12	41.35.39.12.12	41.35.39.22.12
	41.35.14.12.24	41.35.14.22.24	41.35.15.12.24	41.35.15.22.24	41.35.16.12.24	41.35.16.22.24	41.35.19.12.24	41.35.19.22.24
	41.35.24.12.24	41.35.24.22.24	41.35.25.12.24	41.35.25.22.24	41.35.26.12.24	41.35.26.22.24	41.35.29.12.24	41.35.29.22.24
	41.35.34.12.24	41.35.34.22.24	41.35.35.12.24	41.35.35.22.24	41.35.36.12.24	41.35.36.22.24	41.35.39.12.24	41.35.39.22.24


Nomenclature - Illuminated Pushbutton

Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Illuminated Pushbutton - Rectangular

Appearance	Operation	Lamp	Voltage	Contact	Red		Amber			
					IP40	IP65	IP40	IP65		
 <p>Rectangular Illuminated</p>	Momentary	LED	6V	1NO-1NC	41.26.12.11.06	41.26.12.21.06	41.26.13.11.06	41.26.13.21.06		
				2NO-2NC	41.26.22.11.06	41.26.22.21.06	41.26.23.11.06	41.26.23.21.06		
				3NO-3NC	41.26.32.11.06	41.26.32.21.06	41.26.33.11.06	41.26.33.21.06		
			12V	1NO-1NC	41.26.12.11.12	41.26.12.21.12	41.26.13.11.12	41.26.13.21.12		
				2NO-2NC	41.26.22.11.12	41.26.22.21.12	41.26.23.11.12	41.26.23.21.12		
				3NO-3NC	41.26.32.11.12	41.26.32.21.12	41.26.33.11.12	41.26.33.21.12		
		24V	1NO-1NC	41.26.12.11.24	41.26.12.21.24	41.26.13.11.24	41.26.13.21.24			
			2NO-2NC	41.26.22.11.24	41.26.22.21.24	41.26.23.11.24	41.26.23.21.24			
			3NO-3NC	41.26.32.11.24	41.26.32.21.24	41.26.33.11.24	41.26.33.21.24			
		Filament	6V	1NO-1NC	41.26.12.12.06	41.26.12.22.06	41.26.13.12.06	41.26.13.22.06		
				2NO-2NC	41.26.22.12.06	41.26.22.22.06	41.26.23.12.06	41.26.23.22.06		
				3NO-3NC	41.26.32.12.06	41.26.32.22.06	41.26.33.12.06	41.26.33.22.06		
	12V		1NO-1NC	41.26.12.12.12	41.26.12.22.12	41.26.13.12.12	41.26.13.22.12			
			2NO-2NC	41.26.22.12.12	41.26.22.22.12	41.26.23.12.12	41.26.23.22.12			
			3NO-3NC	41.26.32.12.12	41.26.32.22.12	41.26.33.12.12	41.26.33.22.12			
	24V	1NO-1NC	41.26.12.12.24	41.26.12.22.24	41.26.13.12.24	41.26.13.22.24				
		2NO-2NC	41.26.22.12.24	41.26.22.22.24	41.26.23.12.24	41.26.23.22.24				
		3NO-3NC	41.26.32.12.24	41.26.32.22.24	41.26.33.12.24	41.26.33.22.24				
	 <p>Rectangular Illuminated</p>	Maintained	LED	6V	1NO-1NC	41.36.12.11.06	41.36.12.21.06	41.36.13.11.06	41.36.13.21.06	
					2NO-2NC	41.36.22.11.06	41.36.22.21.06	41.36.23.11.06	41.36.23.21.06	
					3NO-3NC	41.36.32.11.06	41.36.32.21.06	41.36.33.11.06	41.36.33.21.06	
				12V	1NO-1NC	41.36.12.11.12	41.36.12.21.12	41.36.13.11.12	41.36.13.21.12	
					2NO-2NC	41.36.22.11.12	41.36.22.21.12	41.36.23.11.12	41.36.23.21.12	
					3NO-3NC	41.36.32.11.12	41.36.32.21.12	41.36.33.11.12	41.36.33.21.12	
24V			1NO-1NC	41.36.12.11.24	41.36.12.21.24	41.36.13.11.24	41.36.13.21.24			
			2NO-2NC	41.36.22.11.24	41.36.22.21.24	41.36.23.11.24	41.36.23.21.24			
			3NO-3NC	41.36.32.11.24	41.36.32.21.24	41.36.33.11.24	41.36.33.21.24			
Filament			6V	1NO-1NC	41.36.12.12.06	41.36.12.22.06	41.36.13.12.06	41.36.13.22.06		
				2NO-2NC	41.36.22.12.06	41.36.22.22.06	41.36.23.12.06	41.36.23.22.06		
				3NO-3NC	41.36.32.12.06	41.36.32.22.06	41.36.33.12.06	41.36.33.22.06		
		12V	1NO-1NC	41.36.12.12.12	41.36.12.22.12	41.36.13.12.12	41.36.13.22.12			
			2NO-2NC	41.36.22.12.12	41.36.22.22.12	41.36.23.12.12	41.36.23.22.12			
			3NO-3NC	41.36.32.12.12	41.36.32.22.12	41.36.33.12.12	41.36.33.22.12			
24V		1NO-1NC	41.36.12.12.24	41.36.12.22.24	41.36.13.12.24	41.36.13.22.24				
		2NO-2NC	41.36.22.12.24	41.36.22.22.24	41.36.23.12.24	41.36.23.22.24				
		3NO-3NC	41.36.32.12.24	41.36.32.22.24	41.36.33.12.24	41.36.33.22.24				

Dimensions - Illuminated Pushbutton



Illuminated Pushbutton - Rectangular

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.26.14.11.06	41.26.14.21.06	41.26.15.11.06	41.26.15.21.06	41.26.16.11.06	41.26.16.21.06	41.26.19.11.06	41.26.19.21.06
	41.26.24.11.06	41.26.24.21.06	41.26.25.11.06	41.26.25.21.06	41.26.26.11.06	41.26.26.21.06	41.26.29.11.06	41.26.29.21.06
	41.26.34.11.06	41.26.34.21.06	41.26.35.11.06	41.26.35.21.06	41.26.36.11.06	41.26.36.21.06	41.26.39.11.06	41.26.39.21.06
	41.26.14.11.12	41.26.14.21.12	41.26.15.11.12	41.26.15.21.12	41.26.16.11.12	41.26.16.21.12	41.26.19.11.12	41.26.19.21.12
	41.26.24.11.12	41.26.24.21.12	41.26.25.11.12	41.26.25.21.12	41.26.26.11.12	41.26.26.21.12	41.26.29.11.12	41.26.29.21.12
	41.26.34.11.12	41.26.34.21.12	41.26.35.11.12	41.26.35.21.12	41.26.36.11.12	41.26.36.21.12	41.26.39.11.12	41.26.39.21.12
	41.26.14.11.24	41.26.14.21.24	41.26.15.11.24	41.26.15.21.24	41.26.16.11.24	41.26.16.21.24	41.26.19.11.24	41.26.19.21.24
	41.26.24.11.24	41.26.24.21.24	41.26.25.11.24	41.26.25.21.24	41.26.26.11.24	41.26.26.21.24	41.26.29.11.24	41.26.29.21.24
	41.26.34.11.24	41.26.34.21.24	41.26.35.11.24	41.26.35.21.24	41.26.36.11.24	41.26.36.21.24	41.26.39.11.24	41.26.39.21.24
	41.26.14.12.06	41.26.14.22.06	41.26.15.12.06	41.26.15.22.06	41.26.16.12.06	41.26.16.22.06	41.26.19.12.06	41.26.19.22.06
	41.26.24.12.06	41.26.24.22.06	41.26.25.12.06	41.26.25.22.06	41.26.26.12.06	41.26.26.22.06	41.26.29.12.06	41.26.29.22.06
	41.26.34.12.06	41.26.34.22.06	41.26.35.12.06	41.26.35.22.06	41.26.36.12.06	41.26.36.22.06	41.26.39.12.06	41.26.39.22.06
	41.26.14.12.12	41.26.14.22.12	41.26.15.12.12	41.26.15.22.12	41.26.16.12.12	41.26.16.22.12	41.26.19.12.12	41.26.19.22.12
	41.26.24.12.12	41.26.24.22.12	41.26.25.12.12	41.26.25.22.12	41.26.26.12.12	41.26.26.22.12	41.26.29.12.12	41.26.29.22.12
	41.26.34.12.12	41.26.34.22.12	41.26.35.12.12	41.26.35.22.12	41.26.36.12.12	41.26.36.22.12	41.26.39.12.12	41.26.39.22.12
	41.26.14.12.24	41.26.14.22.24	41.26.15.12.24	41.26.15.22.24	41.26.16.12.24	41.26.16.22.24	41.26.19.12.24	41.26.19.22.24
	41.26.24.12.24	41.26.24.22.24	41.26.25.12.24	41.26.25.22.24	41.26.26.12.24	41.26.26.22.24	41.26.29.12.24	41.26.29.22.24
	41.26.34.12.24	41.26.34.22.24	41.26.35.12.24	41.26.35.22.24	41.26.36.12.24	41.26.36.22.24	41.26.39.12.24	41.26.39.22.24
	41.36.14.11.06	41.36.14.21.06	41.36.15.11.06	41.36.15.21.06	41.36.16.11.06	41.36.16.21.06	41.36.19.11.06	41.36.19.21.06
	41.36.24.11.06	41.36.24.21.06	41.36.25.11.06	41.36.25.21.06	41.36.26.11.06	41.36.26.21.06	41.36.29.11.06	41.36.29.21.06
	41.36.34.11.06	41.36.34.21.06	41.36.35.11.06	41.36.35.21.06	41.36.36.11.06	41.36.36.21.06	41.36.39.11.06	41.36.39.21.06
	41.36.14.11.12	41.36.14.21.12	41.36.15.11.12	41.36.15.21.12	41.36.16.11.12	41.36.16.21.12	41.36.19.11.12	41.36.19.21.12
	41.36.24.11.12	41.36.24.21.12	41.36.25.11.12	41.36.25.21.12	41.36.26.11.12	41.36.26.21.12	41.36.29.11.12	41.36.29.21.12
	41.36.34.11.12	41.36.34.21.12	41.36.35.11.12	41.36.35.21.12	41.36.36.11.12	41.36.36.21.12	41.36.39.11.12	41.36.39.21.12
	41.36.14.11.24	41.36.14.21.24	41.36.15.11.24	41.36.15.21.24	41.36.16.11.24	41.36.16.21.24	41.36.19.11.24	41.36.19.21.24
	41.36.24.11.24	41.36.24.21.24	41.36.25.11.24	41.36.25.21.24	41.36.26.11.24	41.36.26.21.24	41.36.29.11.24	41.36.29.21.24
	41.36.34.11.24	41.36.34.21.24	41.36.35.11.24	41.36.35.21.24	41.36.36.11.24	41.36.36.21.24	41.36.39.11.24	41.36.39.21.24
	41.36.14.12.06	41.36.14.22.06	41.36.15.12.06	41.36.15.22.06	41.36.16.12.06	41.36.16.22.06	41.36.19.12.06	41.36.19.22.06
	41.36.24.12.06	41.36.24.22.06	41.36.25.12.06	41.36.25.22.06	41.36.26.12.06	41.36.26.22.06	41.36.29.12.06	41.36.29.22.06
	41.36.34.12.06	41.36.34.22.06	41.36.35.12.06	41.36.35.22.06	41.36.36.12.06	41.36.36.22.06	41.36.39.12.06	41.36.39.22.06
	41.36.14.12.12	41.36.14.22.12	41.36.15.12.12	41.36.15.22.12	41.36.16.12.12	41.36.16.22.12	41.36.19.12.12	41.36.19.22.12
	41.36.24.12.12	41.36.24.22.12	41.36.25.12.12	41.36.25.22.12	41.36.26.12.12	41.36.26.22.12	41.36.29.12.12	41.36.29.22.12
	41.36.34.12.12	41.36.34.22.12	41.36.35.12.12	41.36.35.22.12	41.36.36.12.12	41.36.36.22.12	41.36.39.12.12	41.36.39.22.12
	41.36.14.12.24	41.36.14.22.24	41.36.15.12.24	41.36.15.22.24	41.36.16.12.24	41.36.16.22.24	41.36.19.12.24	41.36.19.22.24
	41.36.24.12.24	41.36.24.22.24	41.36.25.12.24	41.36.25.22.24	41.36.26.12.24	41.36.26.22.24	41.36.29.12.24	41.36.29.22.24
	41.36.34.12.24	41.36.34.22.24	41.36.35.12.24	41.36.35.22.24	41.36.36.12.24	41.36.36.22.24	41.36.39.12.24	41.36.39.22.24

Nomenclature - Illuminated Pushbutton

41 Series Switches & Indicators

Operation Type

Shape

Contact

41.26.16.21.12

Blue

Voltage

Lamp type

Protection


Color

Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Illuminated Selector Switch - Round

Appearance	Positions	Voltage	Lamp	Contact	Red		Amber	
					IP40	IP65	IP40	IP65
 <p>90° 2 Positions Round Illuminated</p>	 <p>Maintained</p>	6V AC/DC	LED	1NO-1NC	41.44.12.111.06	41.44.12.211.06	41.44.13.111.06	41.44.13.211.06
				2NO-2NC	41.44.22.111.06	41.44.22.211.06	41.44.23.111.06	41.44.23.211.06
				3NO-3NC	41.44.32.111.06	41.44.32.211.06	41.44.33.111.06	41.44.33.211.06
			Filament	1NO-1NC	41.44.12.112.06	41.44.12.212.06	41.44.13.112.06	41.44.13.212.06
				2NO-2NC	41.44.22.112.06	41.44.22.212.06	41.44.23.112.06	41.44.23.212.06
				3NO-3NC	41.44.32.112.06	41.44.32.212.06	41.44.33.112.06	41.44.33.212.06
	12V AC/DC	LED	1NO-1NC	41.44.12.111.12	41.44.12.211.12	41.44.13.111.12	41.44.13.211.12	
			2NO-2NC	41.44.22.111.12	41.44.22.211.12	41.44.23.111.12	41.44.23.211.12	
			3NO-3NC	41.44.32.111.12	41.44.32.211.12	41.44.33.111.12	41.44.33.211.12	
		Filament	1NO-1NC	41.44.12.112.12	41.44.12.212.12	41.44.13.112.12	41.44.13.212.12	
			2NO-2NC	41.44.22.112.12	41.44.22.212.12	41.44.23.112.12	41.44.23.212.12	
			3NO-3NC	41.44.32.112.12	41.44.32.212.12	41.44.33.112.12	41.44.33.212.12	
24V AC/DC	LED	1NO-1NC	41.44.12.111.24	41.44.12.211.24	41.44.13.111.24	41.44.13.211.24		
		2NO-2NC	41.44.22.111.24	41.44.22.211.24	41.44.23.111.24	41.44.23.211.24		
		3NO-3NC	41.44.32.111.24	41.44.32.211.24	41.44.33.111.24	41.44.33.211.24		
	Filament	1NO-1NC	41.44.12.112.24	41.44.12.212.24	41.44.13.112.24	41.44.13.212.24		
		2NO-2NC	41.44.22.112.24	41.44.22.212.24	41.44.23.112.24	41.44.23.212.24		
		3NO-3NC	41.44.32.112.24	41.44.32.212.24	41.44.33.112.24	41.44.33.212.24		
 <p>90° 2 Positions Round Illuminated</p>	 <p>Spring Return from Right</p>	6V AC/DC	LED	1NO-1NC	41.44.12.121.06	41.44.12.221.06	41.44.13.121.06	41.44.13.221.06
				2NO-2NC	41.44.22.121.06	41.44.22.221.06	41.44.23.121.06	41.44.23.221.06
				3NO-3NC	41.44.32.121.06	41.44.32.221.06	41.44.33.121.06	41.44.33.221.06
			Filament	1NO-1NC	41.44.12.122.06	41.44.12.222.06	41.44.13.122.06	41.44.13.222.06
				2NO-2NC	41.44.22.122.06	41.44.22.222.06	41.44.23.122.06	41.44.23.222.06
				3NO-3NC	41.44.32.122.06	41.44.32.222.06	41.44.33.122.06	41.44.33.222.06
	12V AC/DC	LED	1NO-1NC	41.44.12.121.12	41.44.12.221.12	41.44.13.121.12	41.44.13.221.12	
			2NO-2NC	41.44.22.121.12	41.44.22.221.12	41.44.23.121.12	41.44.23.221.12	
			3NO-3NC	41.44.32.121.12	41.44.32.221.12	41.44.33.121.12	41.44.33.221.12	
		Filament	1NO-1NC	41.44.12.122.12	41.44.12.222.12	41.44.13.122.12	41.44.13.222.12	
			2NO-2NC	41.44.22.122.12	41.44.22.222.12	41.44.23.122.12	41.44.23.222.12	
			3NO-3NC	41.44.32.122.12	41.44.32.222.12	41.44.33.122.12	41.44.33.222.12	
24V AC/DC	LED	1NO-1NC	41.44.12.121.24	41.44.12.221.24	41.44.13.121.24	41.44.13.221.24		
		2NO-2NC	41.44.22.121.24	41.44.22.221.24	41.44.23.121.24	41.44.23.221.24		
		3NO-3NC	41.44.32.121.24	41.44.32.221.24	41.44.33.121.24	41.44.33.221.24		
	Filament	1NO-1NC	41.44.12.122.24	41.44.12.222.24	41.44.13.122.24	41.44.13.222.24		
		2NO-2NC	41.44.22.122.24	41.44.22.222.24	41.44.23.122.24	41.44.23.222.24		
		3NO-3NC	41.44.32.122.24	41.44.32.222.24	41.44.33.122.24	41.44.33.222.24		

Dimensions - Illuminated Selector Switch



Refer to next page for more color selection.

Illuminated Selector Switch - Round

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.44.14.111.06	41.44.14.211.06	41.44.15.111.06	41.44.15.211.06	41.44.16.111.06	41.44.16.211.06	41.44.19.111.06	41.44.19.211.06
	41.44.24.111.06	41.44.24.211.06	41.44.25.111.06	41.44.25.211.06	41.44.26.111.06	41.44.26.211.06	41.44.29.111.06	41.44.29.211.06
	41.44.34.111.06	41.44.34.211.06	41.44.35.111.06	41.44.35.211.06	41.44.36.111.06	41.44.36.211.06	41.44.39.111.06	41.44.39.211.06
	41.44.14.112.06	41.44.14.212.06	41.44.15.112.06	41.44.15.212.06	41.44.16.112.06	41.44.16.212.06	41.44.19.112.06	41.44.19.212.06
	41.44.24.112.06	41.44.24.212.06	41.44.25.112.06	41.44.25.212.06	41.44.26.112.06	41.44.26.212.06	41.44.29.112.06	41.44.29.212.06
	41.44.34.112.06	41.44.34.212.06	41.44.35.112.06	41.44.35.212.06	41.44.36.112.06	41.44.36.212.06	41.44.39.112.06	41.44.39.212.06
	41.44.14.111.12	41.44.14.211.12	41.44.15.111.12	41.44.15.211.12	41.44.16.111.12	41.44.16.211.12	41.44.19.111.12	41.44.19.211.12
	41.44.24.111.12	41.44.24.211.12	41.44.25.111.12	41.44.25.211.12	41.44.26.111.12	41.44.26.211.12	41.44.29.111.12	41.44.29.211.12
	41.44.34.111.12	41.44.34.211.12	41.44.35.111.12	41.44.35.211.12	41.44.36.111.12	41.44.36.211.12	41.44.39.111.12	41.44.39.211.12
	41.44.14.112.12	41.44.14.212.12	41.44.15.112.12	41.44.15.212.12	41.44.16.112.12	41.44.16.212.12	41.44.19.112.12	41.44.19.212.12
	41.44.24.112.12	41.44.24.212.12	41.44.25.112.12	41.44.25.212.12	41.44.26.112.12	41.44.26.212.12	41.44.29.112.12	41.44.29.212.12
	41.44.34.112.12	41.44.34.212.12	41.44.35.112.12	41.44.35.212.12	41.44.36.112.12	41.44.36.212.12	41.44.39.112.12	41.44.39.212.12
	41.44.14.111.24	41.44.14.211.24	41.44.15.111.24	41.44.15.211.24	41.44.16.111.24	41.44.16.211.24	41.44.19.111.24	41.44.19.211.24
	41.44.24.111.24	41.44.24.211.24	41.44.25.111.24	41.44.25.211.24	41.44.26.111.24	41.44.26.211.24	41.44.29.111.24	41.44.29.211.24
	41.44.34.111.24	41.44.34.211.24	41.44.35.111.24	41.44.35.211.24	41.44.36.111.24	41.44.36.211.24	41.44.39.111.24	41.44.39.211.24
	41.44.14.112.24	41.44.14.212.24	41.44.15.112.24	41.44.15.212.24	41.44.16.112.24	41.44.16.212.24	41.44.19.112.24	41.44.19.212.24
	41.44.24.112.24	41.44.24.212.24	41.44.25.112.24	41.44.25.212.24	41.44.26.112.24	41.44.26.212.24	41.44.29.112.24	41.44.29.212.24
	41.44.34.112.24	41.44.34.212.24	41.44.35.112.24	41.44.35.212.24	41.44.36.112.24	41.44.36.212.24	41.44.39.112.24	41.44.39.212.24
	41.44.14.121.06	41.44.14.211.06	41.44.15.121.06	41.44.15.211.06	41.44.16.121.06	41.44.16.211.06	41.44.19.121.06	41.44.19.211.06
	41.44.24.121.06	41.44.24.211.06	41.44.25.121.06	41.44.25.211.06	41.44.26.121.06	41.44.26.211.06	41.44.29.121.06	41.44.29.211.06
	41.44.34.121.06	41.44.34.211.06	41.44.35.121.06	41.44.35.211.06	41.44.36.121.06	41.44.36.211.06	41.44.39.121.06	41.44.39.211.06
	41.44.14.122.06	41.44.14.212.06	41.44.15.122.06	41.44.15.212.06	41.44.16.122.06	41.44.16.212.06	41.44.19.122.06	41.44.19.212.06
	41.44.24.122.06	41.44.24.212.06	41.44.25.122.06	41.44.25.212.06	41.44.26.122.06	41.44.26.212.06	41.44.29.122.06	41.44.29.212.06
	41.44.34.122.06	41.44.34.212.06	41.44.35.122.06	41.44.35.212.06	41.44.36.122.06	41.44.36.212.06	41.44.39.122.06	41.44.39.212.06
	41.44.14.121.12	41.44.14.211.12	41.44.15.121.12	41.44.15.211.12	41.44.16.121.12	41.44.16.211.12	41.44.19.121.12	41.44.19.211.12
	41.44.24.121.12	41.44.24.211.12	41.44.25.121.12	41.44.25.211.12	41.44.26.121.12	41.44.26.211.12	41.44.29.121.12	41.44.29.211.12
	41.44.34.121.12	41.44.34.211.12	41.44.35.121.12	41.44.35.211.12	41.44.36.121.12	41.44.36.211.12	41.44.39.121.12	41.44.39.211.12
	41.44.14.122.12	41.44.14.212.12	41.44.15.122.12	41.44.15.212.12	41.44.16.122.12	41.44.16.212.12	41.44.19.122.12	41.44.19.212.12
	41.44.24.122.12	41.44.24.212.12	41.44.25.122.12	41.44.25.212.12	41.44.26.122.12	41.44.26.212.12	41.44.29.122.12	41.44.29.212.12
	41.44.34.122.12	41.44.34.212.12	41.44.35.122.12	41.44.35.212.12	41.44.36.122.12	41.44.36.212.12	41.44.39.122.12	41.44.39.212.12
	41.44.14.121.24	41.44.14.211.24	41.44.15.121.24	41.44.15.211.24	41.44.16.121.24	41.44.16.211.24	41.44.19.121.24	41.44.19.211.24
	41.44.24.121.24	41.44.24.211.24	41.44.25.121.24	41.44.25.211.24	41.44.26.121.24	41.44.26.211.24	41.44.29.121.24	41.44.29.211.24
	41.44.34.121.24	41.44.34.211.24	41.44.35.121.24	41.44.35.211.24	41.44.36.121.24	41.44.36.211.24	41.44.39.121.24	41.44.39.211.24
	41.44.14.122.24	41.44.14.212.24	41.44.15.122.24	41.44.15.212.24	41.44.16.122.24	41.44.16.212.24	41.44.19.122.24	41.44.19.212.24
	41.44.24.122.24	41.44.24.212.24	41.44.25.122.24	41.44.25.212.24	41.44.26.122.24	41.44.26.212.24	41.44.29.122.24	41.44.29.212.24
	41.44.34.122.24	41.44.34.212.24	41.44.35.122.24	41.44.35.212.24	41.44.36.122.24	41.44.36.212.24	41.44.39.122.24	41.44.39.212.24

Nomenclature - Illuminated Selector Switch



Yellow

41.44.14.121.12

Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

41 Series Switches & Indicators

Selector Switch 2 - Positions

Illuminated Round

SPDT

12 V

LED Lamp

Spring Return from Right

IP40



Illuminated Selector Switch - Round


Appearance	Positions	Voltage	Lamp	Contact	Red		Amber			
					IP40	IP65	IP40	IP65		
 45° 3 Positions Round Illuminated	Maintained 	6V AC/DC	LED	2NO-2NC	41.54.22.111.06	41.54.22.211.06	41.54.23.111.06	41.54.23.211.06		
				3NO-3NC	41.54.32.111.06	41.54.32.211.06	41.54.33.111.06	41.54.33.211.06		
				Filament	2NO-2NC	41.54.22.112.06	41.54.22.212.06	41.54.23.112.06	41.54.23.212.06	
			3NO-3NC	41.54.32.112.06	41.54.32.212.06	41.54.33.112.06	41.54.33.212.06			
			12V AC/DC	LED	2NO-2NC	41.54.22.111.12	41.54.22.211.12	41.54.23.111.12	41.54.23.211.12	
					3NO-3NC	41.54.32.111.12	41.54.32.211.12	41.54.33.111.12	41.54.33.211.12	
		Filament		2NO-2NC	41.54.22.112.12	41.54.22.212.12	41.54.23.112.12	41.54.23.212.12		
		3NO-3NC	41.54.32.112.12	41.54.32.212.12	41.54.33.112.12	41.54.33.212.12				
		24V AC/DC	LED	2NO-2NC	41.54.22.111.24	41.54.22.211.24	41.54.23.111.24	41.54.23.211.24		
				3NO-3NC	41.54.32.111.24	41.54.32.211.24	41.54.33.111.24	41.54.33.211.24		
				Filament	2NO-2NC	41.54.22.112.24	41.54.22.212.24	41.54.23.112.24	41.54.23.212.24	
			3NO-3NC	41.54.32.112.24	41.54.32.212.24	41.54.33.112.24	41.54.33.212.24			
	Spring Return from Right 		6V AC/DC	LED	2NO-2NC	41.54.22.121.06	41.54.22.221.06	41.54.23.121.06	41.54.23.221.06	
					3NO-3NC	41.54.32.121.06	41.54.32.221.06	41.54.33.121.06	41.54.33.221.06	
		Filament	2NO-2NC	41.54.22.122.06	41.54.22.222.06	41.54.23.122.06	41.54.23.222.06			
	3NO-3NC	41.54.32.122.06	41.54.32.222.06	41.54.33.122.06	41.54.33.222.06					
	12V AC/DC	LED	2NO-2NC	41.54.22.121.12	41.54.22.221.12	41.54.23.121.12	41.54.23.221.12			
			3NO-3NC	41.54.32.121.12	41.54.32.221.12	41.54.33.121.12	41.54.33.221.12			
			Filament	2NO-2NC	41.54.22.122.12	41.54.22.222.12	41.54.23.122.12	41.54.23.222.12		
		3NO-3NC	41.54.32.122.12	41.54.32.222.12	41.54.33.122.12	41.54.33.222.12				
		24V AC/DC	LED	2NO-2NC	41.54.22.121.24	41.54.22.221.24	41.54.23.121.24	41.54.23.221.24		
				3NO-3NC	41.54.32.121.24	41.54.32.221.24	41.54.33.121.24	41.54.33.221.24		
	Filament		2NO-2NC	41.54.22.122.24	41.54.22.222.24	41.54.23.122.24	41.54.23.222.24			
	3NO-3NC	41.54.32.122.24	41.54.32.222.24	41.54.33.122.24	41.54.33.222.24					
 45° 3 Positions Round Illuminated	Spring Return from Left 	6V AC/DC	LED	2NO-2NC	41.54.22.131.06	41.54.22.231.06	41.54.23.131.06	41.54.23.231.06		
				3NO-3NC	41.54.32.131.06	41.54.32.231.06	41.54.33.131.06	41.54.33.231.06		
				Filament	2NO-2NC	41.54.22.132.06	41.54.22.232.06	41.54.23.132.06	41.54.23.232.06	
			3NO-3NC	41.54.32.132.06	41.54.32.232.06	41.54.33.132.06	41.54.33.232.06			
			12V AC/DC	LED	2NO-2NC	41.54.22.131.12	41.54.22.231.12	41.54.23.131.12	41.54.23.231.12	
					3NO-3NC	41.54.32.131.12	41.54.32.231.12	41.54.33.131.12	41.54.33.231.12	
		Filament		2NO-2NC	41.54.22.132.12	41.54.22.232.12	41.54.23.132.12	41.54.23.232.12		
		3NO-3NC	41.54.32.132.12	41.54.32.232.12	41.54.33.132.12	41.54.33.232.12				
		24V AC/DC	LED	2NO-2NC	41.54.22.131.24	41.54.22.231.24	41.54.23.131.24	41.54.23.231.24		
				3NO-3NC	41.54.32.131.24	41.54.32.231.24	41.54.33.131.24	41.54.33.231.24		
				Filament	2NO-2NC	41.54.22.132.24	41.54.22.232.24	41.54.23.132.24	41.54.23.232.24	
			3NO-3NC	41.54.32.132.24	41.54.32.232.24	41.54.33.132.24	41.54.33.232.24			
	Spring Return Two Ways 		6V AC/DC	LED	2NO-2NC	41.54.22.141.06	41.54.22.241.06	41.54.23.141.06	41.54.23.241.06	
					3NO-3NC	41.54.32.141.06	41.54.32.241.06	41.54.33.141.06	41.54.33.241.06	
		Filament	2NO-2NC	41.54.22.142.06	41.54.22.242.06	41.54.23.142.06	41.54.23.242.06			
	3NO-3NC	41.54.32.142.06	41.54.32.242.06	41.54.33.142.06	41.54.33.242.06					
	12V AC/DC	LED	2NO-2NC	41.54.22.141.12	41.54.22.241.12	41.54.23.141.12	41.54.23.241.12			
			3NO-3NC	41.54.32.141.12	41.54.32.241.12	41.54.33.141.12	41.54.33.241.12			
			Filament	2NO-2NC	41.54.22.142.12	41.54.22.242.12	41.54.23.142.12	41.54.23.242.12		
		3NO-3NC	41.54.32.142.12	41.54.32.242.12	41.54.33.142.12	41.54.33.242.12				
		24V AC/DC	LED	2NO-2NC	41.54.22.141.24	41.54.22.241.24	41.54.23.141.24	41.54.23.241.24		
				3NO-3NC	41.54.32.141.24	41.54.32.241.24	41.54.33.141.24	41.54.33.241.24		
	Filament		2NO-2NC	41.54.22.142.24	41.54.22.242.24	41.54.23.142.24	41.54.23.242.24			
	3NO-3NC	41.54.32.142.24	41.54.32.242.24	41.54.33.142.24	41.54.33.242.24					

Refer to next page for more color selection.

Illuminated Selector Switch - Square

Appearance	Positions	Voltage	Lamp	Contact	Red		Amber	
					IP40	IP65	IP40	IP65
 <p>90° 2 Positions Square Illuminated</p>	 <p>Maintained</p>	6V AC/DC	LED	1NO-1NC	41.45.12.111.06	41.45.12.211.06	41.45.13.111.06	41.45.13.211.06
				2NO-2NC	41.45.22.111.06	41.45.22.211.06	41.45.23.111.06	41.45.23.211.06
				3NO-3NC	41.45.32.111.06	41.45.32.211.06	41.45.33.111.06	41.45.33.211.06
			Filament	1NO-1NC	41.45.12.112.06	41.45.12.212.06	41.45.13.112.06	41.45.13.212.06
				2NO-2NC	41.45.22.112.06	41.45.22.212.06	41.45.23.112.06	41.45.23.212.06
				3NO-3NC	41.45.32.112.06	41.45.32.212.06	41.45.33.112.06	41.45.33.212.06
	12V AC/DC	LED	1NO-1NC	41.45.12.111.12	41.45.12.211.12	41.45.13.111.12	41.45.13.211.12	
			2NO-2NC	41.45.22.111.12	41.45.22.211.12	41.45.23.111.12	41.45.23.211.12	
			3NO-3NC	41.45.32.111.12	41.45.32.211.12	41.45.33.111.12	41.45.33.211.12	
		Filament	1NO-1NC	41.45.12.112.12	41.45.12.212.12	41.45.13.112.12	41.45.13.212.12	
			2NO-2NC	41.45.22.112.12	41.45.22.212.12	41.45.23.112.12	41.45.23.212.12	
			3NO-3NC	41.45.32.112.12	41.45.32.212.12	41.45.33.112.12	41.45.33.212.12	
24V AC/DC	LED	1NO-1NC	41.45.12.111.24	41.45.12.211.24	41.45.13.111.24	41.45.13.211.24		
		2NO-2NC	41.45.22.111.24	41.45.22.211.24	41.45.23.111.24	41.45.23.211.24		
		3NO-3NC	41.45.32.111.24	41.45.32.211.24	41.45.33.111.24	41.45.33.211.24		
	Filament	1NO-1NC	41.45.12.112.24	41.45.12.212.24	41.45.13.112.24	41.45.13.212.24		
		2NO-2NC	41.45.22.112.24	41.45.22.212.24	41.45.23.112.24	41.45.23.212.24		
		3NO-3NC	41.45.32.112.24	41.45.32.212.24	41.45.33.112.24	41.45.33.212.24		
 <p>90° 2 Positions Square Illuminated</p>	 <p>Spring Return from Right</p>	6V AC/DC	LED	1NO-1NC	41.45.12.121.06	41.45.12.221.06	41.45.13.121.06	41.45.13.221.06
				2NO-2NC	41.45.22.121.06	41.45.22.221.06	41.45.23.121.06	41.45.23.221.06
				3NO-3NC	41.45.32.121.06	41.45.32.221.06	41.45.33.121.06	41.45.33.221.06
			Filament	1NO-1NC	41.45.12.122.06	41.45.12.222.06	41.45.13.122.06	41.45.13.222.06
				2NO-2NC	41.45.22.122.06	41.45.22.222.06	41.45.23.122.06	41.45.23.222.06
				3NO-3NC	41.45.32.122.06	41.45.32.222.06	41.45.33.122.06	41.45.33.222.06
	12V AC/DC	LED	1NO-1NC	41.45.12.121.12	41.45.12.221.12	41.45.13.121.12	41.45.13.221.12	
			2NO-2NC	41.45.22.121.12	41.45.22.221.12	41.45.23.121.12	41.45.23.221.12	
			3NO-3NC	41.45.32.121.12	41.45.32.221.12	41.45.33.121.12	41.45.33.221.12	
		Filament	1NO-1NC	41.45.12.122.12	41.45.12.222.12	41.45.13.122.12	41.45.13.222.12	
			2NO-2NC	41.45.22.122.12	41.45.22.222.12	41.45.23.122.12	41.45.23.222.12	
			3NO-3NC	41.45.32.122.12	41.45.32.222.12	41.45.33.122.12	41.45.33.222.12	
24V AC/DC	LED	1NO-1NC	41.45.12.121.24	41.45.12.221.24	41.45.13.121.24	41.45.13.221.24		
		2NO-2NC	41.45.22.121.24	41.45.22.221.24	41.45.23.121.24	41.45.23.221.24		
		3NO-3NC	41.45.32.121.24	41.45.32.221.24	41.45.33.121.24	41.45.33.221.24		
	Filament	1NO-1NC	41.45.12.122.24	41.45.12.222.24	41.45.13.122.24	41.45.13.222.24		
		2NO-2NC	41.45.22.122.24	41.45.22.222.24	41.45.23.122.24	41.45.23.222.24		
		3NO-3NC	41.45.32.122.24	41.45.32.222.24	41.45.33.122.24	41.45.33.222.24		

Dimensions - Illuminated Selector Switch



Refer to next page for more color selection.



Illuminated Selector Switch - Square


Appearance	Positions	Voltage	Lamp	Contact	Red		Amber			
					IP40	IP65	IP40	IP65		
 <p>45° 3 Positions Square Illuminated</p>	<p>Maintained</p> 	6V AC/DC	LED	2NO-2NC	41.55.22.111.06	41.55.22.211.06	41.55.23.111.06	41.55.23.211.06		
				3NO-3NC	41.55.32.111.06	41.55.32.211.06	41.55.33.111.06	41.55.33.211.06		
				Filament	2NO-2NC	41.55.22.112.06	41.55.22.212.06	41.55.23.112.06	41.55.23.212.06	
				3NO-3NC	41.55.32.112.06	41.55.32.212.06	41.55.33.112.06	41.55.33.212.06		
			12V AC/DC	LED	2NO-2NC	41.55.22.111.12	41.55.22.211.12	41.55.23.111.12	41.55.23.211.12	
					3NO-3NC	41.55.32.111.12	41.55.32.211.12	41.55.33.111.12	41.55.33.211.12	
		Filament	2NO-2NC	41.55.22.112.12	41.55.22.212.12	41.55.23.112.12	41.55.23.212.12			
				3NO-3NC	41.55.32.112.12	41.55.32.212.12	41.55.33.112.12	41.55.33.212.12		
		24V AC/DC	LED	2NO-2NC	41.55.22.111.24	41.55.22.211.24	41.55.23.111.24	41.55.23.211.24		
				3NO-3NC	41.55.32.111.24	41.55.32.211.24	41.55.33.111.24	41.55.33.211.24		
				Filament	2NO-2NC	41.55.22.112.24	41.55.22.212.24	41.55.23.112.24	41.55.23.212.24	
				3NO-3NC	41.55.32.112.24	41.55.32.212.24	41.55.33.112.24	41.55.33.212.24		
	12V AC/DC		LED	2NO-2NC	41.55.22.121.06	41.55.22.221.06	41.55.23.121.06	41.55.23.221.06		
				3NO-3NC	41.55.32.121.06	41.55.32.221.06	41.55.33.121.06	41.55.33.221.06		
	Filament	2NO-2NC	41.55.22.122.06	41.55.22.222.06	41.55.23.122.06	41.55.23.222.06				
			3NO-3NC	41.55.32.122.06	41.55.32.222.06	41.55.33.122.06	41.55.33.222.06			
	24V AC/DC	LED	2NO-2NC	41.55.22.121.12	41.55.22.221.12	41.55.23.121.12	41.55.23.221.12			
			3NO-3NC	41.55.32.121.12	41.55.32.221.12	41.55.33.121.12	41.55.33.221.12			
			Filament	2NO-2NC	41.55.22.122.12	41.55.22.222.12	41.55.23.122.12	41.55.23.222.12		
			3NO-3NC	41.55.32.122.12	41.55.32.222.12	41.55.33.122.12	41.55.33.222.12			
		24V AC/DC	LED	2NO-2NC	41.55.22.121.24	41.55.22.221.24	41.55.23.121.24	41.55.23.221.24		
				3NO-3NC	41.55.32.121.24	41.55.32.221.24	41.55.33.121.24	41.55.33.221.24		
	Filament	2NO-2NC	41.55.22.122.24	41.55.22.222.24	41.55.23.122.24	41.55.23.222.24				
			3NO-3NC	41.55.32.122.24	41.55.32.222.24	41.55.33.122.24	41.55.33.222.24			
 <p>45° 3 Positions Square Illuminated</p>	<p>Spring Return from Left</p> 	6V AC/DC	LED	2NO-2NC	41.55.22.131.06	41.55.22.231.06	41.55.23.131.06	41.55.23.231.06		
				3NO-3NC	41.55.32.131.06	41.55.32.231.06	41.55.33.131.06	41.55.33.231.06		
				Filament	2NO-2NC	41.55.22.132.06	41.55.22.232.06	41.55.23.132.06	41.55.23.232.06	
				3NO-3NC	41.55.32.132.06	41.55.32.232.06	41.55.33.132.06	41.55.33.232.06		
			12V AC/DC	LED	2NO-2NC	41.55.22.131.12	41.55.22.231.12	41.55.23.131.12	41.55.23.231.12	
					3NO-3NC	41.55.32.131.12	41.55.32.231.12	41.55.33.131.12	41.55.33.231.12	
		Filament	2NO-2NC	41.55.22.132.12	41.55.22.232.12	41.55.23.132.12	41.55.23.232.12			
				3NO-3NC	41.55.32.132.12	41.55.32.232.12	41.55.33.132.12	41.55.33.232.12		
		24V AC/DC	LED	2NO-2NC	41.55.22.131.24	41.55.22.231.24	41.55.23.131.24	41.55.23.231.24		
				3NO-3NC	41.55.32.131.24	41.55.32.231.24	41.55.33.131.24	41.55.33.231.24		
				Filament	2NO-2NC	41.55.22.132.24	41.55.22.232.24	41.55.23.132.24	41.55.23.232.24	
				3NO-3NC	41.55.32.132.24	41.55.32.232.24	41.55.33.132.24	41.55.33.232.24		
	6V AC/DC		LED	2NO-2NC	41.55.22.141.06	41.55.22.241.06	41.55.23.141.06	41.55.23.241.06		
				3NO-3NC	41.55.32.141.06	41.55.32.241.06	41.55.33.141.06	41.55.33.241.06		
	Filament	2NO-2NC	41.55.22.142.06	41.55.22.242.06	41.55.23.142.06	41.55.23.242.06				
			3NO-3NC	41.55.32.142.06	41.55.32.242.06	41.55.33.142.06	41.55.33.242.06			
	12V AC/DC	LED	2NO-2NC	41.55.22.141.12	41.55.22.241.12	41.55.23.141.12	41.55.23.241.12			
			3NO-3NC	41.55.32.141.12	41.55.32.241.12	41.55.33.141.12	41.55.33.241.12			
		Filament	2NO-2NC	41.55.22.142.12	41.55.22.242.12	41.55.23.142.12	41.55.23.242.12			
				3NO-3NC	41.55.32.142.12	41.55.32.242.12	41.55.33.142.12	41.55.33.242.12		
		24V AC/DC	LED	2NO-2NC	41.55.22.141.24	41.55.22.241.24	41.55.23.141.24	41.55.23.241.24		
				3NO-3NC	41.55.32.141.24	41.55.32.241.24	41.55.33.141.24	41.55.33.241.24		
	Filament	2NO-2NC	41.55.22.142.24	41.55.22.242.24	41.55.23.142.24	41.55.23.242.24				
			3NO-3NC	41.55.32.142.24	41.55.32.242.24	41.55.33.142.24	41.55.33.242.24			

Refer to next page for more color selection.

Illuminated Selector Switch - Rectangular

Appearance	Positions	Voltage	Lamp	Contact	Red		Amber	
					IP40	IP65	IP40	IP65
 <p>90° 2 Positions Rectangular Illuminated</p>	 <p>Maintained</p>	6V AC/DC	LED	1NO-1NC	41.46.12.111.06	41.46.12.211.06	41.46.13.111.06	41.46.13.211.06
				2NO-2NC	41.46.22.111.06	41.46.22.211.06	41.46.23.111.06	41.46.23.211.06
				3NO-3NC	41.46.32.111.06	41.46.32.211.06	41.46.33.111.06	41.46.33.211.06
			Filament	1NO-1NC	41.46.12.112.06	41.46.12.212.06	41.46.13.112.06	41.46.13.212.06
				2NO-2NC	41.46.22.112.06	41.46.22.212.06	41.46.23.112.06	41.46.23.212.06
				3NO-3NC	41.46.32.112.06	41.46.32.212.06	41.46.33.112.06	41.46.33.212.06
	12V AC/DC	LED	1NO-1NC	41.46.12.111.12	41.46.12.211.12	41.46.13.111.12	41.46.13.211.12	
			2NO-2NC	41.46.22.111.12	41.46.22.211.12	41.46.23.111.12	41.46.23.211.12	
			3NO-3NC	41.46.32.111.12	41.46.32.211.12	41.46.33.111.12	41.46.33.211.12	
		Filament	1NO-1NC	41.46.12.112.12	41.46.12.212.12	41.46.13.112.12	41.46.13.212.12	
			2NO-2NC	41.46.22.112.12	41.46.22.212.12	41.46.23.112.12	41.46.23.212.12	
			3NO-3NC	41.46.32.112.12	41.46.32.212.12	41.46.33.112.12	41.46.33.212.12	
24V AC/DC	LED	1NO-1NC	41.46.12.111.24	41.46.12.211.24	41.46.13.111.24	41.46.13.211.24		
		2NO-2NC	41.46.22.111.24	41.46.22.211.24	41.46.23.111.24	41.46.23.211.24		
		3NO-3NC	41.46.32.111.24	41.46.32.211.24	41.46.33.111.24	41.46.33.211.24		
	Filament	1NO-1NC	41.46.12.112.24	41.46.12.212.24	41.46.13.112.24	41.46.13.212.24		
		2NO-2NC	41.46.22.112.24	41.46.22.212.24	41.46.23.112.24	41.46.23.212.24		
		3NO-3NC	41.46.32.112.24	41.46.32.212.24	41.46.33.112.24	41.46.33.212.24		
 <p>90° 2 Positions Rectangular Illuminated</p>	 <p>Spring Return from Right</p>	6V AC/DC	LED	1NO-1NC	41.46.12.121.06	41.46.12.221.06	41.46.13.121.06	41.46.13.221.06
				2NO-2NC	41.46.22.121.06	41.46.22.221.06	41.46.23.121.06	41.46.23.221.06
				3NO-3NC	41.46.32.121.06	41.46.32.221.06	41.46.33.121.06	41.46.33.221.06
			Filament	1NO-1NC	41.46.12.122.06	41.46.12.222.06	41.46.13.122.06	41.46.13.222.06
				2NO-2NC	41.46.22.122.06	41.46.22.222.06	41.46.23.122.06	41.46.23.222.06
				3NO-3NC	41.46.32.122.06	41.46.32.222.06	41.46.33.122.06	41.46.33.222.06
	12V AC/DC	LED	1NO-1NC	41.46.12.121.12	41.46.12.221.12	41.46.13.121.12	41.46.13.221.12	
			2NO-2NC	41.46.22.121.12	41.46.22.221.12	41.46.23.121.12	41.46.23.221.12	
			3NO-3NC	41.46.32.121.12	41.46.32.221.12	41.46.33.121.12	41.46.33.221.12	
		Filament	1NO-1NC	41.46.12.122.12	41.46.12.222.12	41.46.13.122.12	41.46.13.222.12	
			2NO-2NC	41.46.22.122.12	41.46.22.222.12	41.46.23.122.12	41.46.23.222.12	
			3NO-3NC	41.46.32.122.12	41.46.32.222.12	41.46.33.122.12	41.46.33.222.12	
24V AC/DC	LED	1NO-1NC	41.46.12.121.24	41.46.12.221.24	41.46.13.121.24	41.46.13.221.24		
		2NO-2NC	41.46.22.121.24	41.46.22.221.24	41.46.23.121.24	41.46.23.221.24		
		3NO-3NC	41.46.32.121.24	41.46.32.221.24	41.46.33.121.24	41.46.33.221.24		
	Filament	1NO-1NC	41.46.12.122.24	41.46.12.222.24	41.46.13.122.24	41.46.13.222.24		
		2NO-2NC	41.46.22.122.24	41.46.22.222.24	41.46.23.122.24	41.46.23.222.24		
		3NO-3NC	41.46.32.122.24	41.46.32.222.24	41.46.33.122.24	41.46.33.222.24		

Dimensions - Illuminated Selector Switch




Refer to next page for more color selection.

Illuminated Selector Switch - Rectangular

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.46.14.111.06	41.46.14.211.06	41.46.15.111.06	41.46.15.211.06	41.46.16.111.06	41.46.16.211.06	41.46.19.111.06	41.46.19.211.06
	41.46.24.111.06	41.46.24.211.06	41.46.25.111.06	41.46.25.211.06	41.46.26.111.06	41.46.26.211.06	41.46.29.111.06	41.46.29.211.06
	41.46.34.111.06	41.46.34.211.06	41.46.35.111.06	41.46.35.211.06	41.46.36.111.06	41.46.36.211.06	41.46.39.111.06	41.46.39.211.06
	41.46.14.112.06	41.46.14.212.06	41.46.15.112.06	41.46.15.212.06	41.46.16.112.06	41.46.16.212.06	41.46.19.112.06	41.46.19.212.06
	41.46.24.112.06	41.46.24.212.06	41.46.25.112.06	41.46.25.212.06	41.46.26.112.06	41.46.26.212.06	41.46.29.112.06	41.46.29.212.06
	41.46.34.112.06	41.46.34.212.06	41.46.35.112.06	41.46.35.212.06	41.46.36.112.06	41.46.36.212.06	41.46.39.112.06	41.46.39.212.06
	41.46.14.111.12	41.46.14.211.12	41.46.15.111.12	41.46.15.211.12	41.46.16.111.12	41.46.16.211.12	41.46.19.111.12	41.46.19.211.12
	41.46.24.111.12	41.46.24.211.12	41.46.25.111.12	41.46.25.211.12	41.46.26.111.12	41.46.26.211.12	41.46.29.111.12	41.46.29.211.12
	41.46.34.111.12	41.46.34.211.12	41.46.35.111.12	41.46.35.211.12	41.46.36.111.12	41.46.36.211.12	41.46.39.111.12	41.46.39.211.12
	41.46.14.112.12	41.46.14.212.12	41.46.15.112.12	41.46.15.212.12	41.46.16.112.12	41.46.16.212.12	41.46.19.112.12	41.46.19.212.12
	41.46.24.112.12	41.46.24.212.12	41.46.25.112.12	41.46.25.212.12	41.46.26.112.12	41.46.26.212.12	41.46.29.112.12	41.46.29.212.12
	41.46.34.112.12	41.46.34.212.12	41.46.35.112.12	41.46.35.212.12	41.46.36.112.12	41.46.36.212.12	41.46.39.112.12	41.46.39.212.12
	41.46.14.111.24	41.46.14.211.24	41.46.15.111.24	41.46.15.211.24	41.46.16.111.24	41.46.16.211.24	41.46.19.111.24	41.46.19.211.24
	41.46.24.111.24	41.46.24.211.24	41.46.25.111.24	41.46.25.211.24	41.46.26.111.24	41.46.26.211.24	41.46.29.111.24	41.46.29.211.24
	41.46.34.111.24	41.46.34.211.24	41.46.35.111.24	41.46.35.211.24	41.46.36.111.24	41.46.36.211.24	41.46.39.111.24	41.46.39.211.24
	41.46.14.112.24	41.46.14.212.24	41.46.15.112.24	41.46.15.212.24	41.46.16.112.24	41.46.16.212.24	41.46.19.112.24	41.46.19.212.24
	41.46.24.112.24	41.46.24.212.24	41.46.25.112.24	41.46.25.212.24	41.46.26.112.24	41.46.26.212.24	41.46.29.112.24	41.46.29.212.24
	41.46.34.112.24	41.46.34.212.24	41.46.35.112.24	41.46.35.212.24	41.46.36.112.24	41.46.36.212.24	41.46.39.112.24	41.46.39.212.24
	41.46.14.121.06	41.46.14.211.06	41.46.15.121.06	41.46.15.211.06	41.46.16.121.06	41.46.16.211.06	41.46.19.121.06	41.46.19.211.06
	41.46.24.121.06	41.46.24.211.06	41.46.25.121.06	41.46.25.211.06	41.46.26.121.06	41.46.26.211.06	41.46.29.121.06	41.46.29.211.06
	41.46.34.121.06	41.46.34.211.06	41.46.35.121.06	41.46.35.211.06	41.46.36.121.06	41.46.36.211.06	41.46.39.121.06	41.46.39.211.06
	41.46.14.122.06	41.46.14.212.06	41.46.15.122.06	41.46.15.212.06	41.46.16.122.06	41.46.16.212.06	41.46.19.122.06	41.46.19.212.06
	41.46.24.122.06	41.46.24.212.06	41.46.25.122.06	41.46.25.212.06	41.46.26.122.06	41.46.26.212.06	41.46.29.122.06	41.46.29.212.06
	41.46.34.122.06	41.46.34.212.06	41.46.35.122.06	41.46.35.212.06	41.46.36.122.06	41.46.36.212.06	41.46.39.122.06	41.46.39.212.06
	41.46.14.121.12	41.46.14.211.12	41.46.15.121.12	41.46.15.211.12	41.46.16.121.12	41.46.16.211.12	41.46.19.121.12	41.46.19.211.12
	41.46.24.121.12	41.46.24.211.12	41.46.25.121.12	41.46.25.211.12	41.46.26.121.12	41.46.26.211.12	41.46.29.121.12	41.46.29.211.12
	41.46.34.121.12	41.46.34.211.12	41.46.35.121.12	41.46.35.211.12	41.46.36.121.12	41.46.36.211.12	41.46.39.121.12	41.46.39.211.12
	41.46.14.122.12	41.46.14.212.12	41.46.15.122.12	41.46.15.212.12	41.46.16.122.12	41.46.16.212.12	41.46.19.122.12	41.46.19.212.12
	41.46.24.122.12	41.46.24.212.12	41.46.25.122.12	41.46.25.212.12	41.46.26.122.12	41.46.26.212.12	41.46.29.122.12	41.46.29.212.12
	41.46.34.122.12	41.46.34.212.12	41.46.35.122.12	41.46.35.212.12	41.46.36.122.12	41.46.36.212.12	41.46.39.122.12	41.46.39.212.12
	41.46.14.121.24	41.46.14.211.24	41.46.15.121.24	41.46.15.211.24	41.46.16.121.24	41.46.16.211.24	41.46.19.121.24	41.46.19.211.24
	41.46.24.121.24	41.46.24.211.24	41.46.25.121.24	41.46.25.211.24	41.46.26.121.24	41.46.26.211.24	41.46.29.121.24	41.46.29.211.24
	41.46.34.121.24	41.46.34.211.24	41.46.35.121.24	41.46.35.211.24	41.46.36.121.24	41.46.36.211.24	41.46.39.121.24	41.46.39.211.24
	41.46.14.122.24	41.46.14.212.24	41.46.15.122.24	41.46.15.212.24	41.46.16.122.24	41.46.16.212.24	41.46.19.122.24	41.46.19.212.24
	41.46.24.122.24	41.46.24.212.24	41.46.25.122.24	41.46.25.212.24	41.46.26.122.24	41.46.26.212.24	41.46.29.122.24	41.46.29.212.24
	41.46.34.122.24	41.46.34.212.24	41.46.35.122.24	41.46.35.212.24	41.46.36.122.24	41.46.36.212.24	41.46.39.122.24	41.46.39.212.24

Nomenclature - Illuminated Selector Switch



Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Illuminated Selector Switch - Rectangular







Appearance	Positions	Voltage	Lamp	Contact	Red		Amber			
					IP40	IP65	IP40	IP65		
<p>45° 3 Positions Rectangular Illuminated</p>	Maintained 	6V AC/DC	LED	2NO-2NC	41.56.22.111.06	41.56.22.211.06	41.56.23.111.06	41.56.23.211.06		
				3NO-3NC	41.56.32.111.06	41.56.32.211.06	41.56.33.111.06	41.56.33.211.06		
				Filament	2NO-2NC	41.56.22.112.06	41.56.22.212.06	41.56.23.112.06	41.56.23.212.06	
				3NO-3NC	41.56.32.112.06	41.56.32.212.06	41.56.33.112.06	41.56.33.212.06		
			12V AC/DC	LED	2NO-2NC	41.56.22.111.12	41.56.22.211.12	41.56.23.111.12	41.56.23.211.12	
					3NO-3NC	41.56.32.111.12	41.56.32.211.12	41.56.33.111.12	41.56.33.211.12	
		Filament			2NO-2NC	41.56.22.112.12	41.56.22.212.12	41.56.23.112.12	41.56.23.212.12	
				3NO-3NC	41.56.32.112.12	41.56.32.212.12	41.56.33.112.12	41.56.33.212.12		
		24V AC/DC	LED	2NO-2NC	41.56.22.111.24	41.56.22.211.24	41.56.23.111.24	41.56.23.211.24		
				3NO-3NC	41.56.32.111.24	41.56.32.211.24	41.56.33.111.24	41.56.33.211.24		
				Filament	2NO-2NC	41.56.22.112.24	41.56.22.212.24	41.56.23.112.24	41.56.23.212.24	
				3NO-3NC	41.56.32.112.24	41.56.32.212.24	41.56.33.112.24	41.56.33.212.24		
	12V AC/DC		LED	2NO-2NC	41.56.22.121.06	41.56.22.221.06	41.56.23.121.06	41.56.23.221.06		
				3NO-3NC	41.56.32.121.06	41.56.32.221.06	41.56.33.121.06	41.56.33.221.06		
		Filament		2NO-2NC	41.56.22.122.06	41.56.22.222.06	41.56.23.122.06	41.56.23.222.06		
			3NO-3NC	41.56.32.122.06	41.56.32.222.06	41.56.33.122.06	41.56.33.222.06			
	24V AC/DC	LED	2NO-2NC	41.56.22.121.12	41.56.22.221.12	41.56.23.121.12	41.56.23.221.12			
			3NO-3NC	41.56.32.121.12	41.56.32.221.12	41.56.33.121.12	41.56.33.221.12			
			Filament	2NO-2NC	41.56.22.122.12	41.56.22.222.12	41.56.23.122.12	41.56.23.222.12		
			3NO-3NC	41.56.32.122.12	41.56.32.222.12	41.56.33.122.12	41.56.33.222.12			
		24V AC/DC	LED	2NO-2NC	41.56.22.121.24	41.56.22.221.24	41.56.23.121.24	41.56.23.221.24		
				3NO-3NC	41.56.32.121.24	41.56.32.221.24	41.56.33.121.24	41.56.33.221.24		
	Filament			2NO-2NC	41.56.22.122.24	41.56.22.222.24	41.56.23.122.24	41.56.23.222.24		
			3NO-3NC	41.56.32.122.24	41.56.32.222.24	41.56.33.122.24	41.56.33.222.24			
<p>45° 3 Positions Rectangular Illuminated</p>	Spring Return from Left 	6V AC/DC	LED	2NO-2NC	41.56.22.131.06	41.56.22.231.06	41.56.23.131.06	41.56.23.231.06		
				3NO-3NC	41.56.32.131.06	41.56.32.231.06	41.56.33.131.06	41.56.33.231.06		
				Filament	2NO-2NC	41.56.22.132.06	41.56.22.232.06	41.56.23.132.06	41.56.23.232.06	
				3NO-3NC	41.56.32.132.06	41.56.32.232.06	41.56.33.132.06	41.56.33.232.06		
			12V AC/DC	LED	2NO-2NC	41.56.22.131.12	41.56.22.231.12	41.56.23.131.12	41.56.23.231.12	
					3NO-3NC	41.56.32.131.12	41.56.32.231.12	41.56.33.131.12	41.56.33.231.12	
		Filament			2NO-2NC	41.56.22.132.12	41.56.22.232.12	41.56.23.132.12	41.56.23.232.12	
				3NO-3NC	41.56.32.132.12	41.56.32.232.12	41.56.33.132.12	41.56.33.232.12		
		24V AC/DC	LED	2NO-2NC	41.56.22.131.24	41.56.22.231.24	41.56.23.131.24	41.56.23.231.24		
				3NO-3NC	41.56.32.131.24	41.56.32.231.24	41.56.33.131.24	41.56.33.231.24		
				Filament	2NO-2NC	41.56.22.132.24	41.56.22.232.24	41.56.23.132.24	41.56.23.232.24	
				3NO-3NC	41.56.32.132.24	41.56.32.232.24	41.56.33.132.24	41.56.33.232.24		
	6V AC/DC		LED	2NO-2NC	41.56.22.141.06	41.56.22.241.06	41.56.23.141.06	41.56.23.241.06		
				3NO-3NC	41.56.32.141.06	41.56.32.241.06	41.56.33.141.06	41.56.33.241.06		
		Filament		2NO-2NC	41.56.22.142.06	41.56.22.242.06	41.56.23.142.06	41.56.23.242.06		
			3NO-3NC	41.56.32.142.06	41.56.32.242.06	41.56.33.142.06	41.56.33.242.06			
	12V AC/DC	LED	2NO-2NC	41.56.22.141.12	41.56.22.241.12	41.56.23.141.12	41.56.23.241.12			
			3NO-3NC	41.56.32.141.12	41.56.32.241.12	41.56.33.141.12	41.56.33.241.12			
			Filament	2NO-2NC	41.56.22.142.12	41.56.22.242.12	41.56.23.142.12	41.56.23.242.12		
			3NO-3NC	41.56.32.142.12	41.56.32.242.12	41.56.33.142.12	41.56.33.242.12			
	24V AC/DC	LED	2NO-2NC	41.56.22.141.24	41.56.22.241.24	41.56.23.141.24	41.56.23.241.24			
			3NO-3NC	41.56.32.141.24	41.56.32.241.24	41.56.33.141.24	41.56.33.241.24			
			Filament	2NO-2NC	41.56.22.142.24	41.56.22.242.24	41.56.23.142.24	41.56.23.242.24		
			3NO-3NC	41.56.32.142.24	41.56.32.242.24	41.56.33.142.24	41.56.33.242.24			

Refer to next page for more color selection.

Selector Switch





Appearance	Position	Operation	Retained at	Contact	Model No.	
					IP40	IP65
 Round	90° 2 Positions	Maintained		1NO-1NC	41.41.10.11	41.41.10.21
				2NO-2NC	41.41.20.11	41.41.20.21
				3NO-3NC	41.41.30.11	41.41.30.21
		Spring Return from Right to Left		1NO-1NC	41.41.10.12	41.41.10.22
				2NO-2NC	41.41.20.12	41.41.20.22
				3NO-3NC	41.41.30.12	41.41.30.22
 Round	45° 3 Positions	Maintained		2NO-2NC	41.51.20.11	41.51.20.21
				3NO-3NC	41.51.30.11	41.51.30.21
		Spring return from right to center		2NO-2NC	41.51.20.12	41.51.20.22
				3NO-3NC	41.51.30.12	41.51.30.22
		Spring return from left to center		2NO-2NC	41.51.20.13	41.51.20.23
				3NO-3NC	41.51.30.13	41.51.30.23
		Spring return two-way		2NO-2NC	41.51.20.14	41.51.20.24
				3NO-3NC	41.51.30.14	41.51.30.24
 Square	90° 2 Positions	Maintained		1NO-1NC	41.42.10.11	41.42.10.21
				2NO-2NC	41.42.20.11	41.42.20.21
				3NO-3NC	41.42.30.11	41.42.30.21
		Spring Return from Right to Left		1NO-1NC	41.42.10.12	41.42.10.22
				2NO-2NC	41.42.20.12	41.42.20.22
				3NO-3NC	41.42.30.12	41.42.30.22
 Square	45° 3 Positions	Maintained		2NO-2NC	41.52.20.11	41.52.20.21
				3NO-3NC	41.52.30.11	41.52.30.21
		Spring return from right to center		2NO-2NC	41.52.20.12	41.52.20.22
				3NO-3NC	41.52.30.12	41.52.30.22
		Spring return from left to center		2NO-2NC	41.52.20.13	41.52.20.23
				3NO-3NC	41.52.30.13	41.52.30.23
		Spring return two-way		2NO-2NC	41.52.20.14	41.52.20.24
				3NO-3NC	41.52.30.14	41.52.30.24
 Rectangular	90° 2 Positions	Maintained		1NO-1NC	41.43.10.11	41.43.10.21
				2NO-2NC	41.43.20.11	41.43.20.21
				3NO-3NC	41.43.30.11	41.43.30.21
		Spring Return from Right to Left		1NO-1NC	41.43.10.12	41.43.10.22
				2NO-2NC	41.43.20.12	41.43.20.22
				3NO-3NC	41.43.30.12	41.43.30.22
 Rectangular	45° 3 Positions	Maintained		2NO-2NC	41.53.20.11	41.53.20.21
				3NO-3NC	41.53.30.11	41.53.30.21
		Spring return from right to center		2NO-2NC	41.53.20.12	41.53.20.22
				3NO-3NC	41.53.30.12	41.53.30.22
		Spring return from left to center		2NO-2NC	41.53.20.13	41.53.20.23
				3NO-3NC	41.53.30.13	41.53.30.23
		Spring return two-way		2NO-2NC	41.53.20.14	41.53.20.24
				3NO-3NC	41.53.30.14	41.53.30.24

Key Selector Switch

Appearance	Position	Operation	Color	Retained at	Contact	Model No.	
						IP40	IP65
 Round	90° 2 Positions	Maintained	Black		1NO-1NC	41.61.10.111	41.61.10.211
					2NO-2NC	41.61.20.111	41.61.20.211
					3NO-3NC	41.61.30.111	41.61.30.211
					1NO-1NC	41.61.10.112	41.61.10.212
					2NO-2NC	41.61.20.112	41.61.20.212
					3NO-3NC	41.61.30.112	41.61.30.212
			1NO-1NC	41.61.10.113	41.61.10.213		
			2NO-2NC	41.61.20.113	41.61.20.213		
			3NO-3NC	41.61.30.113	41.61.30.213		
		Spring Return from Right to Left	Black		1NO-1NC	41.61.10.122	41.61.10.222
					2NO-2NC	41.61.20.122	41.61.20.222
					3NO-3NC	41.61.30.122	41.61.30.222
 Round	45° 3 Positions	Maintained	Black		2NO-2NC	41.71.20.111	41.71.20.211
					3NO-3NC	41.71.30.111	41.71.30.211
					2NO-2NC	41.71.20.112	41.71.20.212
					3NO-3NC	41.71.30.112	41.71.30.212
					2NO-2NC	41.71.20.113	41.71.20.213
					3NO-3NC	41.71.30.113	41.71.30.213
					2NO-2NC	41.71.20.114	41.71.20.214
					3NO-3NC	41.71.30.114	41.71.30.214
					2NO-2NC	41.71.20.115	41.71.20.215
					3NO-3NC	41.71.30.115	41.71.30.215
					2NO-2NC	41.71.20.116	41.71.20.216
					3NO-3NC	41.71.30.116	41.71.30.216
			2NO-2NC	41.71.20.117	41.71.20.217		
			3NO-3NC	41.71.30.117	41.71.30.217		
		Spring Return from Right to Center	Black		2NO-2NC	41.71.20.122	41.71.20.222
					3NO-3NC	41.71.30.122	41.71.30.222
					2NO-2NC	41.71.20.124	41.71.20.224
					3NO-3NC	41.71.30.124	41.71.30.224
					2NO-2NC	41.71.20.126	41.71.20.226
					3NO-3NC	41.71.30.126	41.71.30.226
		Spring Return from Left to Center	Black		2NO-2NC	41.71.20.133	41.71.20.233
					3NO-3NC	41.71.30.133	41.71.30.233
					2NO-2NC	41.71.20.134	41.71.20.234
					3NO-3NC	41.71.30.134	41.71.30.234
	2NO-2NC			41.71.20.137	41.71.20.237		
	3NO-3NC			41.71.30.137	41.71.30.237		
Spring Return two ways	Black		2NO-2NC	41.71.20.144	41.71.20.244		
			3NO-3NC	41.71.30.144	41.71.30.244		







Key is retained at ● positions and removable at ○ position.
 Each 41 Series Key Selector Switch is supplied with a spare key.

Key Selector Switch

Appearance	Position	Operation	Color	Retained at	Contact	Model No.	
						IP40	IP65
 <p>Square</p>	90° 2 Positions	Maintained	Black		1NO-1NC	41.62.10.111	41.62.10.211
					2NO-2NC	41.62.20.111	41.62.20.211
					3NO-3NC	41.62.30.111	41.62.30.211
					1NO-1NC	41.62.10.112	41.62.10.212
					2NO-2NC	41.62.20.112	41.62.20.212
					3NO-3NC	41.62.30.112	41.62.30.212
			1NO-1NC	41.62.10.113	41.62.10.213		
			2NO-2NC	41.62.20.113	41.62.20.213		
			3NO-3NC	41.62.30.113	41.62.30.213		
		Spring Return from Right to Left	Black		1NO-1NC	41.62.10.122	41.62.10.222
					2NO-2NC	41.62.20.122	41.62.20.222
					3NO-3NC	41.62.30.122	41.62.30.222
 <p>Square</p>	45° 3 Positions	Maintained	Black		2NO-2NC	41.72.20.111	41.72.20.211
					3NO-3NC	41.72.30.111	41.72.30.211
					2NO-2NC	41.72.20.112	41.72.20.212
					3NO-3NC	41.72.30.112	41.72.30.212
					2NO-2NC	41.72.20.113	41.72.20.213
					3NO-3NC	41.72.30.113	41.72.30.213
					2NO-2NC	41.72.20.114	41.72.20.214
					3NO-3NC	41.72.30.114	41.72.30.214
					2NO-2NC	41.72.20.115	41.72.20.215
					3NO-3NC	41.72.30.115	41.72.30.215
					2NO-2NC	41.72.20.116	41.72.20.216
					3NO-3NC	41.72.30.116	41.72.30.216
			2NO-2NC	41.72.20.117	41.72.20.217		
			3NO-3NC	41.72.30.117	41.72.30.217		
		Spring Return from Right to Center	Black		2NO-2NC	41.72.20.122	41.72.20.222
					3NO-3NC	41.72.30.122	41.72.30.222
					2NO-2NC	41.72.20.124	41.72.20.224
					3NO-3NC	41.72.30.124	41.72.30.224
					2NO-2NC	41.72.20.126	41.72.20.226
					3NO-3NC	41.72.30.126	41.72.30.226
		Spring Return from Left to Center	Black		2NO-2NC	41.72.20.133	41.72.20.233
					3NO-3NC	41.72.30.133	41.72.30.233
					2NO-2NC	41.72.20.134	41.72.20.234
					3NO-3NC	41.72.30.134	41.72.30.234
	2NO-2NC			41.72.20.137	41.72.20.237		
	3NO-3NC			41.72.30.137	41.72.30.237		
Spring Return two ways	Black		2NO-2NC	41.72.20.144	41.72.20.244		
			3NO-3NC	41.72.30.144	41.72.30.244		

Key is retained at ● positions and removable at ○ position.
Each 41 Series Key Selector Switch is supplied with a spare key.

Key Selector Switch


Appearance	Position	Operation	Color	Retained at	Contact	Model No.	
						IP40	IP65
 Rectangular	90° 2 Positions	Maintained	Black		1NO-1NC	41.63.10.111	41.63.10.211
					2NO-2NC	41.63.20.111	41.63.20.211
					3NO-3NC	41.63.30.111	41.63.30.211
					1NO-1NC	41.63.10.112	41.63.10.212
					2NO-2NC	41.63.20.112	41.63.20.212
					3NO-3NC	41.63.30.112	41.63.30.212
			1NO-1NC	41.63.10.113	41.63.10.213		
			2NO-2NC	41.63.20.113	41.63.20.213		
			3NO-3NC	41.63.30.113	41.63.30.213		
		Spring Return from Right to Left	Black		1NO-1NC	41.63.10.122	41.63.10.222
					2NO-2NC	41.63.20.122	41.63.20.222
					3NO-3NC	41.63.30.122	41.63.30.222
 Rectangular	45° 3 Positions	Maintained	Black		2NO-2NC	41.73.20.111	41.73.20.211
					3NO-3NC	41.73.30.111	41.73.30.211
					2NO-2NC	41.73.20.112	41.73.20.212
					3NO-3NC	41.73.30.112	41.73.30.212
					2NO-2NC	41.73.20.113	41.73.20.213
					3NO-3NC	41.73.30.113	41.73.30.213
					2NO-2NC	41.73.20.114	41.73.20.214
					3NO-3NC	41.73.30.114	41.73.30.214
					2NO-2NC	41.73.20.115	41.73.20.215
					3NO-3NC	41.73.30.115	41.73.30.215
					2NO-2NC	41.73.20.116	41.73.20.216
					3NO-3NC	41.73.30.116	41.73.30.216
			2NO-2NC	41.73.20.117	41.73.20.217		
			3NO-3NC	41.73.30.117	41.73.30.217		
		Spring Return from Right to Center	Black		2NO-2NC	41.73.20.122	41.73.20.222
					3NO-3NC	41.73.30.122	41.73.30.222
					2NO-2NC	41.73.20.124	41.73.20.224
					3NO-3NC	41.73.30.124	41.73.30.224
					2NO-2NC	41.73.20.126	41.73.20.226
					3NO-3NC	41.73.30.126	41.73.30.226
		Spring Return from Left to Center	Black		2NO-2NC	41.73.20.133	41.73.20.233
					3NO-3NC	41.73.30.133	41.73.30.233
					2NO-2NC	41.73.20.134	41.73.20.234
					3NO-3NC	41.73.30.134	41.73.30.234
	2NO-2NC			41.73.20.137	41.73.20.237		
	3NO-3NC			41.73.30.137	41.73.30.237		
Spring Return two ways	Black		2NO-2NC	41.73.20.144	41.73.20.244		
			3NO-3NC	41.73.30.144	41.73.30.244		

Key is retained at ● positions and removable at ○ position.
 Each 41 Series Key Selector Switch is supplied with a spare key.

Mushroom Head Pushbutton

Appearance	Operation	Type	Contact	Red		Amber		Yellow
				IP40	IP65	IP40	IP65	IP40
 Round	Momentary	Opaque Button	1NO-1NC	41.81.12.10.00	41.81.12.20.00	41.81.13.10.00	41.81.13.20.00	41.81.14.10.00
			2NO-2NC	41.81.22.10.00	41.81.22.20.00	41.81.23.10.00	41.81.23.20.00	41.81.24.10.00
			3NO-3NC	41.81.32.10.00	41.81.32.20.00	41.81.33.10.00	41.81.33.20.00	41.81.34.10.00
		Illuminated Lens	1NO-1NC	41.84.12.10.00	41.84.12.20.00	41.84.13.10.00	41.84.13.20.00	41.84.14.10.00
			2NO-2NC	41.84.22.10.00	41.84.22.20.00	41.84.23.10.00	41.84.23.20.00	41.84.24.10.00
			3NO-3NC	41.84.32.10.00	41.84.32.20.00	41.84.33.10.00	41.84.33.20.00	41.84.34.10.00
	Maintained	Opaque Button	1NO-1NC	41.91.12.10.00	41.91.12.20.00	41.91.13.10.00	41.91.13.20.00	41.91.14.10.00
			2NO-2NC	41.91.22.10.00	41.91.22.20.00	41.91.23.10.00	41.91.23.20.00	41.91.24.10.00
			3NO-3NC	41.91.32.10.00	41.91.32.20.00	41.91.33.10.00	41.91.33.20.00	41.91.34.10.00
		Illuminated Lens	1NO-1NC	41.94.12.10.00	41.94.12.20.00	41.94.13.10.00	41.94.13.20.00	41.94.14.10.00
			2NO-2NC	41.94.22.10.00	41.94.22.20.00	41.94.23.10.00	41.94.23.20.00	41.94.24.10.00
			3NO-3NC	41.94.32.10.00	41.94.32.20.00	41.94.33.10.00	41.94.33.20.00	41.94.34.10.00
 Square	Momentary	Opaque Button	1NO-1NC	41.82.12.10.00	41.82.12.20.00	41.82.13.10.00	41.82.13.20.00	41.82.14.10.00
			2NO-2NC	41.82.22.10.00	41.82.22.20.00	41.82.23.10.00	41.82.23.20.00	41.82.24.10.00
			3NO-3NC	41.82.32.10.00	41.82.32.20.00	41.82.33.10.00	41.82.33.20.00	41.82.34.10.00
		Illuminated Lens	1NO-1NC	41.85.12.10.00	41.85.12.20.00	41.85.13.10.00	41.85.13.20.00	41.85.14.10.00
			2NO-2NC	41.85.22.10.00	41.85.22.20.00	41.85.23.10.00	41.85.23.20.00	41.85.24.10.00
			3NO-3NC	41.85.32.10.00	41.85.32.20.00	41.85.33.10.00	41.85.33.20.00	41.85.34.10.00
	Maintained	Opaque Button	1NO-1NC	41.92.12.10.00	41.92.12.20.00	41.92.13.10.00	41.92.13.20.00	41.92.14.10.00
			2NO-2NC	41.92.22.10.00	41.92.22.20.00	41.92.23.10.00	41.92.23.20.00	41.92.24.10.00
			3NO-3NC	41.92.32.10.00	41.92.32.20.00	41.92.33.10.00	41.92.33.20.00	41.92.34.10.00
		Illuminated Lens	1NO-1NC	41.95.12.10.00	41.95.12.20.00	41.95.13.10.00	41.95.13.20.00	41.95.14.10.00
			2NO-2NC	41.95.22.10.00	41.95.22.20.00	41.95.23.10.00	41.95.23.20.00	41.95.24.10.00
			3NO-3NC	41.95.32.10.00	41.95.32.20.00	41.95.33.10.00	41.95.33.20.00	41.95.34.10.00
 Rectangular	Momentary	Opaque Button	1NO-1NC	41.83.12.10.00	41.83.12.20.00	41.83.13.10.00	41.83.13.20.00	41.83.14.10.00
			2NO-2NC	41.83.22.10.00	41.83.22.20.00	41.83.23.10.00	41.83.23.20.00	41.83.24.10.00
			3NO-3NC	41.83.32.10.00	41.83.32.20.00	41.83.33.10.00	41.83.33.20.00	41.83.34.10.00
		Illuminated Lens	1NO-1NC	41.86.12.10.00	41.86.12.20.00	41.86.13.10.00	41.86.13.20.00	41.86.14.10.00
			2NO-2NC	41.86.22.10.00	41.86.22.20.00	41.86.23.10.00	41.86.23.20.00	41.86.24.10.00
			3NO-3NC	41.86.32.10.00	41.86.32.20.00	41.86.33.10.00	41.86.33.20.00	41.86.34.10.00
	Maintained	Opaque Button	1NO-1NC	41.93.12.10.00	41.93.12.20.00	41.93.13.10.00	41.93.13.20.00	41.93.14.10.00
			2NO-2NC	41.93.22.10.00	41.93.22.20.00	41.93.23.10.00	41.93.23.20.00	41.93.24.10.00
			3NO-3NC	41.93.32.10.00	41.93.32.20.00	41.93.33.10.00	41.93.33.20.00	41.93.34.10.00
		Illuminated Lens	1NO-1NC	41.96.12.10.00	41.96.12.20.00	41.96.13.10.00	41.96.13.20.00	41.96.14.10.00
			2NO-2NC	41.96.22.10.00	41.96.22.20.00	41.96.23.10.00	41.96.23.20.00	41.96.24.10.00
			3NO-3NC	41.96.32.10.00	41.96.32.20.00	41.96.33.10.00	41.96.33.20.00	41.96.34.10.00

Dimensions - Non-Illuminated Mushroom Head Pushbutton



Refer to next page for more color selection.

Mushroom Head Pushbutton

Yellow		Green		Blue		White		Black	
IP65	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65	
41.81.14.20.00	41.81.15.10.00	41.81.15.20.00	41.81.16.10.00	41.81.16.20.00	41.81.19.10.00	41.81.19.20.00	41.81.10.10.00	41.81.10.20.00	
41.81.24.20.00	41.81.25.10.00	41.81.25.20.00	41.81.26.10.00	41.81.26.20.00	41.81.29.10.00	41.81.29.20.00	41.81.20.10.00	41.81.20.20.00	
41.81.34.20.00	41.81.35.10.00	41.81.35.20.00	41.81.36.10.00	41.81.36.20.00	41.81.39.10.00	41.81.39.20.00	41.81.30.10.00	41.81.30.20.00	
41.84.14.20.00	41.84.15.10.00	41.84.15.20.00	41.84.16.10.00	41.84.16.20.00	41.84.19.10.00	41.84.19.20.00	41.84.10.10.00	41.84.10.20.00	
41.84.24.20.00	41.84.25.10.00	41.84.25.20.00	41.84.26.10.00	41.84.26.20.00	41.84.29.10.00	41.84.29.20.00	41.84.20.10.00	41.84.20.20.00	
41.84.34.20.00	41.84.35.10.00	41.84.35.20.00	41.84.36.10.00	41.84.36.20.00	41.84.39.10.00	41.84.39.20.00	41.84.30.10.00	41.84.30.20.00	
41.91.14.20.00	41.91.15.10.00	41.91.15.20.00	41.91.16.10.00	41.91.16.20.00	41.91.19.10.00	41.91.19.20.00	41.91.10.10.00	41.91.10.20.00	
41.91.24.20.00	41.91.25.10.00	41.91.25.20.00	41.91.26.10.00	41.91.26.20.00	41.91.29.10.00	41.91.29.20.00	41.91.20.10.00	41.91.20.20.00	
41.91.34.20.00	41.91.35.10.00	41.91.35.20.00	41.91.36.10.00	41.91.36.20.00	41.91.39.10.00	41.91.39.20.00	41.91.30.10.00	41.91.30.20.00	
41.94.14.20.00	41.94.15.10.00	41.94.15.20.00	41.94.16.10.00	41.94.16.20.00	41.94.19.10.00	41.94.19.20.00	41.94.10.10.00	41.94.10.20.00	
41.94.24.20.00	41.94.25.10.00	41.94.25.20.00	41.94.26.10.00	41.94.26.20.00	41.94.29.10.00	41.94.29.20.00	41.94.20.10.00	41.94.20.20.00	
41.94.34.20.00	41.94.35.10.00	41.94.35.20.00	41.94.36.10.00	41.94.36.20.00	41.94.39.10.00	41.94.39.20.00	41.94.30.10.00	41.94.30.20.00	
41.82.14.20.00	41.82.15.10.00	41.82.15.20.00	41.82.16.10.00	41.82.16.20.00	41.82.19.10.00	41.82.19.20.00	41.82.10.10.00	41.82.10.20.00	
41.82.24.20.00	41.82.25.10.00	41.82.25.20.00	41.82.26.10.00	41.82.26.20.00	41.82.29.10.00	41.82.29.20.00	41.82.20.10.00	41.82.20.20.00	
41.82.34.20.00	41.82.35.10.00	41.82.35.20.00	41.82.36.10.00	41.82.36.20.00	41.82.39.10.00	41.82.39.20.00	41.82.30.10.00	41.82.30.20.00	
41.85.14.20.00	41.85.15.10.00	41.85.15.20.00	41.85.16.10.00	41.85.16.20.00	41.85.19.10.00	41.85.19.20.00	41.85.10.10.00	41.85.10.20.00	
41.85.24.20.00	41.85.25.10.00	41.85.25.20.00	41.85.26.10.00	41.85.26.20.00	41.85.29.10.00	41.85.29.20.00	41.85.20.10.00	41.85.20.20.00	
41.85.34.20.00	41.85.35.10.00	41.85.35.20.00	41.85.36.10.00	41.85.36.20.00	41.85.39.10.00	41.85.39.20.00	41.85.30.10.00	41.85.30.20.00	
41.92.14.20.00	41.92.15.10.00	41.92.15.20.00	41.92.16.10.00	41.92.16.20.00	41.92.19.10.00	41.92.19.20.00	41.92.10.10.00	41.92.10.20.00	
41.92.24.20.00	41.92.25.10.00	41.92.25.20.00	41.92.26.10.00	41.92.26.20.00	41.92.29.10.00	41.92.29.20.00	41.92.20.10.00	41.92.20.20.00	
41.92.34.20.00	41.92.35.10.00	41.92.35.20.00	41.92.36.10.00	41.92.36.20.00	41.92.39.10.00	41.92.39.20.00	41.92.30.10.00	41.92.30.20.00	
41.95.14.20.00	41.95.15.10.00	41.95.15.20.00	41.95.16.10.00	41.95.16.20.00	41.95.19.10.00	41.95.19.20.00	41.95.10.10.00	41.95.10.20.00	
41.95.24.20.00	41.95.25.10.00	41.95.25.20.00	41.95.26.10.00	41.95.26.20.00	41.95.29.10.00	41.95.29.20.00	41.95.20.10.00	41.95.20.20.00	
41.95.34.20.00	41.95.35.10.00	41.95.35.20.00	41.95.36.10.00	41.95.36.20.00	41.95.39.10.00	41.95.39.20.00	41.95.30.10.00	41.95.30.20.00	
41.83.14.20.00	41.83.15.10.00	41.83.15.20.00	41.83.16.10.00	41.83.16.20.00	41.83.19.10.00	41.83.19.20.00	41.83.10.10.00	41.83.10.20.00	
41.83.24.20.00	41.83.25.10.00	41.83.25.20.00	41.83.26.10.00	41.83.26.20.00	41.83.29.10.00	41.83.29.20.00	41.83.20.10.00	41.83.20.20.00	
41.83.34.20.00	41.83.35.10.00	41.83.35.20.00	41.83.36.10.00	41.83.36.20.00	41.83.39.10.00	41.83.39.20.00	41.83.30.10.00	41.83.30.20.00	
41.86.14.20.00	41.86.15.10.00	41.86.15.20.00	41.86.16.10.00	41.86.16.20.00	41.86.19.10.00	41.86.19.20.00	41.86.10.10.00	41.86.10.20.00	
41.86.24.20.00	41.86.25.10.00	41.86.25.20.00	41.86.26.10.00	41.86.26.20.00	41.86.29.10.00	41.86.29.20.00	41.86.20.10.00	41.86.20.20.00	
41.86.34.20.00	41.86.35.10.00	41.86.35.20.00	41.86.36.10.00	41.86.36.20.00	41.86.39.10.00	41.86.39.20.00	41.86.30.10.00	41.86.30.20.00	
41.93.14.20.00	41.93.15.10.00	41.93.15.20.00	41.93.16.10.00	41.93.16.20.00	41.93.19.10.00	41.93.19.20.00	41.93.10.10.00	41.93.10.20.00	
41.93.24.20.00	41.93.25.10.00	41.93.25.20.00	41.93.26.10.00	41.93.26.20.00	41.93.29.10.00	41.93.29.20.00	41.93.20.10.00	41.93.20.20.00	
41.93.34.20.00	41.93.35.10.00	41.93.35.20.00	41.93.36.10.00	41.93.36.20.00	41.93.39.10.00	41.93.39.20.00	41.93.30.10.00	41.93.30.20.00	
41.96.14.20.00	41.96.15.10.00	41.96.15.20.00	41.96.16.10.00	41.96.16.20.00	41.96.19.10.00	41.96.19.20.00	41.96.10.10.00	41.96.10.20.00	
41.96.24.20.00	41.96.25.10.00	41.96.25.20.00	41.96.26.10.00	41.96.26.20.00	41.96.29.10.00	41.96.29.20.00	41.96.20.10.00	41.96.20.20.00	
41.96.34.20.00	41.96.35.10.00	41.96.35.20.00	41.96.36.10.00	41.96.36.20.00	41.96.39.10.00	41.96.39.20.00	41.96.30.10.00	41.96.30.20.00	

Nomenclature - Non-Illuminated Mushroom Head Pushbutton

Amber

41.91.13.12.12

41 Series Switches & Indicators

Operation Type

Shape

Contact

Voltage

Lamp type


Protection

Color

Illuminated Mushroom Head Pushbutton - Round

Appearance	Operation	Lamp	Voltage	Contact	Red		Amber	
					IP40	IP65	IP40	IP65
 <p>Round Illuminated</p>	Momentary	LED	6V	1NO-1NC	41.84.12.11.06	41.84.12.21.06	41.84.13.11.06	41.84.13.21.06
				2NO-2NC	41.84.22.11.06	41.84.22.21.06	41.84.23.11.06	41.84.23.21.06
				3NO-3NC	41.84.32.11.06	41.84.32.21.06	41.84.33.11.06	41.84.33.21.06
			12V	1NO-1NC	41.84.12.11.12	41.84.12.21.12	41.84.13.11.12	41.84.13.21.12
				2NO-2NC	41.84.22.11.12	41.84.22.21.12	41.84.23.11.12	41.84.23.21.12
				3NO-3NC	41.84.32.11.12	41.84.32.21.12	41.84.33.11.12	41.84.33.21.12
		24V	1NO-1NC	41.84.12.11.24	41.84.12.21.24	41.84.13.11.24	41.84.13.21.24	
			2NO-2NC	41.84.22.11.24	41.84.22.21.24	41.84.23.11.24	41.84.23.21.24	
			3NO-3NC	41.84.32.11.24	41.84.32.21.24	41.84.33.11.24	41.84.33.21.24	
		Filament	6V	1NO-1NC	41.84.12.12.06	41.84.12.22.06	41.84.13.12.06	41.84.13.22.06
				2NO-2NC	41.84.22.12.06	41.84.22.22.06	41.84.23.12.06	41.84.23.22.06
				3NO-3NC	41.84.32.12.06	41.84.32.22.06	41.84.33.12.06	41.84.33.22.06
	12V		1NO-1NC	41.84.12.12.12	41.84.12.22.12	41.84.13.12.12	41.84.13.22.12	
			2NO-2NC	41.84.22.12.12	41.84.22.22.12	41.84.23.12.12	41.84.23.22.12	
			3NO-3NC	41.84.32.12.12	41.84.32.22.12	41.84.33.12.12	41.84.33.22.12	
	24V	1NO-1NC	41.84.12.12.24	41.84.12.22.24	41.84.13.12.24	41.84.13.22.24		
		2NO-2NC	41.84.22.12.24	41.84.22.22.24	41.84.23.12.24	41.84.23.22.24		
		3NO-3NC	41.84.32.12.24	41.84.32.22.24	41.84.33.12.24	41.84.33.22.24		
 <p>Round Illuminated</p>	Maintained	LED	6V	1NO-1NC	41.94.12.11.06	41.94.12.21.06	41.94.13.11.06	41.94.13.21.06
				2NO-2NC	41.94.22.11.06	41.94.22.21.06	41.94.23.11.06	41.94.23.21.06
				3NO-3NC	41.94.32.11.06	41.94.32.21.06	41.94.33.11.06	41.94.33.21.06
			12V	1NO-1NC	41.94.12.11.12	41.94.12.21.12	41.94.13.11.12	41.94.13.21.12
				2NO-2NC	41.94.22.11.12	41.94.22.21.12	41.94.23.11.12	41.94.23.21.12
				3NO-3NC	41.94.32.11.12	41.94.32.21.12	41.94.33.11.12	41.94.33.21.12
		24V	1NO-1NC	41.94.12.11.24	41.94.12.21.24	41.94.13.11.24	41.94.13.21.24	
			2NO-2NC	41.94.22.11.24	41.94.22.21.24	41.94.23.11.24	41.94.23.21.24	
			3NO-3NC	41.94.32.11.24	41.94.32.21.24	41.94.33.11.24	41.94.33.21.24	
		Filament	6V	1NO-1NC	41.94.12.12.06	41.94.12.22.06	41.94.13.12.06	41.94.13.22.06
				2NO-2NC	41.94.22.12.06	41.94.22.22.06	41.94.23.12.06	41.94.23.22.06
				3NO-3NC	41.94.32.12.06	41.94.32.22.06	41.94.33.12.06	41.94.33.22.06
	12V		1NO-1NC	41.94.12.12.12	41.94.12.22.12	41.94.13.12.12	41.94.13.22.12	
			2NO-2NC	41.94.22.12.12	41.94.22.22.12	41.94.23.12.12	41.94.23.22.12	
			3NO-3NC	41.94.32.12.12	41.94.32.22.12	41.94.33.12.12	41.94.33.22.12	
	24V	1NO-1NC	41.94.12.12.24	41.94.12.22.24	41.94.13.12.24	41.94.13.22.24		
		2NO-2NC	41.94.22.12.24	41.94.22.22.24	41.94.23.12.24	41.94.23.22.24		
		3NO-3NC	41.94.32.12.24	41.94.32.22.24	41.94.33.12.24	41.94.33.22.24		

Dimensions - Illuminated Mushroom Head Pushbutton



Refer to next page for more color selection.

Illuminated Mushroom Head Pushbutton - Round

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.84.14.11.06	41.84.14.21.06	41.84.15.11.06	41.84.15.21.06	41.84.16.11.06	41.84.16.21.06	41.84.19.11.06	41.84.19.21.06
	41.84.24.11.06	41.84.24.21.06	41.84.25.11.06	41.84.25.21.06	41.84.26.11.06	41.84.26.21.06	41.84.29.11.06	41.84.29.21.06
	41.84.34.11.06	41.84.34.21.06	41.84.35.11.06	41.84.35.21.06	41.84.36.11.06	41.84.36.21.06	41.84.39.11.06	41.84.39.21.06
	41.84.14.11.12	41.84.14.21.12	41.84.15.11.12	41.84.15.21.12	41.84.16.11.12	41.84.16.21.12	41.84.19.11.12	41.84.19.21.12
	41.84.24.11.12	41.84.24.21.12	41.84.25.11.12	41.84.25.21.12	41.84.26.11.12	41.84.26.21.12	41.84.29.11.12	41.84.29.21.12
	41.84.34.11.12	41.84.34.21.12	41.84.35.11.12	41.84.35.21.12	41.84.36.11.12	41.84.36.21.12	41.84.39.11.12	41.84.39.21.12
	41.84.14.11.24	41.84.14.21.24	41.84.15.11.24	41.84.15.21.24	41.84.16.11.24	41.84.16.21.24	41.84.19.11.24	41.84.19.21.24
	41.84.24.11.24	41.84.24.21.24	41.84.25.11.24	41.84.25.21.24	41.84.26.11.24	41.84.26.21.24	41.84.29.11.24	41.84.29.21.24
	41.84.34.11.24	41.84.34.21.24	41.84.35.11.24	41.84.35.21.24	41.84.36.11.24	41.84.36.21.24	41.84.39.11.24	41.84.39.21.24
	41.84.14.12.06	41.84.14.22.06	41.84.15.12.06	41.84.15.22.06	41.84.16.12.06	41.84.16.22.06	41.84.19.12.06	41.84.19.22.06
	41.84.24.12.06	41.84.24.22.06	41.84.25.12.06	41.84.25.22.06	41.84.26.12.06	41.84.26.22.06	41.84.29.12.06	41.84.29.22.06
	41.84.34.12.06	41.84.34.22.06	41.84.35.12.06	41.84.35.22.06	41.84.36.12.06	41.84.36.22.06	41.84.39.12.06	41.84.39.22.06
	41.84.14.12.12	41.84.14.22.12	41.84.15.12.12	41.84.15.22.12	41.84.16.12.12	41.84.16.22.12	41.84.19.12.12	41.84.19.22.12
	41.84.24.12.12	41.84.24.22.12	41.84.25.12.12	41.84.25.22.12	41.84.26.12.12	41.84.26.22.12	41.84.29.12.12	41.84.29.22.12
	41.84.34.12.12	41.84.34.22.12	41.84.35.12.12	41.84.35.22.12	41.84.36.12.12	41.84.36.22.12	41.84.39.12.12	41.84.39.22.12
	41.84.14.12.24	41.84.14.22.24	41.84.15.12.24	41.84.15.22.24	41.84.16.12.24	41.84.16.22.24	41.84.19.12.24	41.84.19.22.24
	41.84.24.12.24	41.84.24.22.24	41.84.25.12.24	41.84.25.22.24	41.84.26.12.24	41.84.26.22.24	41.84.29.12.24	41.84.29.22.24
	41.84.34.12.24	41.84.34.22.24	41.84.35.12.24	41.84.35.22.24	41.84.36.12.24	41.84.36.22.24	41.84.39.12.24	41.84.39.22.24
	41.94.14.11.06	41.94.14.21.06	41.94.15.11.06	41.94.15.21.06	41.94.16.11.06	41.94.16.21.06	41.94.19.11.06	41.94.19.21.06
	41.94.24.11.06	41.94.24.21.06	41.94.25.11.06	41.94.25.21.06	41.94.26.11.06	41.94.26.21.06	41.94.29.11.06	41.94.29.21.06
	41.94.34.11.06	41.94.34.21.06	41.94.35.11.06	41.94.35.21.06	41.94.36.11.06	41.94.36.21.06	41.94.39.11.06	41.94.39.21.06
	41.94.14.11.12	41.94.14.21.12	41.94.15.11.12	41.94.15.21.12	41.94.16.11.12	41.94.16.21.12	41.94.19.11.12	41.94.19.21.12
	41.94.24.11.12	41.94.24.21.12	41.94.25.11.12	41.94.25.21.12	41.94.26.11.12	41.94.26.21.12	41.94.29.11.12	41.94.29.21.12
	41.94.34.11.12	41.94.34.21.12	41.94.35.11.12	41.94.35.21.12	41.94.36.11.12	41.94.36.21.12	41.94.39.11.12	41.94.39.21.12
	41.94.14.11.24	41.94.14.21.24	41.94.15.11.24	41.94.15.21.24	41.94.16.11.24	41.94.16.21.24	41.94.19.11.24	41.94.19.21.24
	41.94.24.11.24	41.94.24.21.24	41.94.25.11.24	41.94.25.21.24	41.94.26.11.24	41.94.26.21.24	41.94.29.11.24	41.94.29.21.24
	41.94.34.11.24	41.94.34.21.24	41.94.35.11.24	41.94.35.21.24	41.94.36.11.24	41.94.36.21.24	41.94.39.11.24	41.94.39.21.24
	41.94.14.12.06	41.94.14.22.06	41.94.15.12.06	41.94.15.22.06	41.94.16.12.06	41.94.16.22.06	41.94.19.12.06	41.94.19.22.06
	41.94.24.12.06	41.94.24.22.06	41.94.25.12.06	41.94.25.22.06	41.94.26.12.06	41.94.26.22.06	41.94.29.12.06	41.94.29.22.06
	41.94.34.12.06	41.94.34.22.06	41.94.35.12.06	41.94.35.22.06	41.94.36.12.06	41.94.36.22.06	41.94.39.12.06	41.94.39.22.06
	41.94.14.12.12	41.94.14.22.12	41.94.15.12.12	41.94.15.22.12	41.94.16.12.12	41.94.16.22.12	41.94.19.12.12	41.94.19.22.12
	41.94.24.12.12	41.94.24.22.12	41.94.25.12.12	41.94.25.22.12	41.94.26.12.12	41.94.26.22.12	41.94.29.12.12	41.94.29.22.12
	41.94.34.12.12	41.94.34.22.12	41.94.35.12.12	41.94.35.22.12	41.94.36.12.12	41.94.36.22.12	41.94.39.12.12	41.94.39.22.12
	41.94.14.12.24	41.94.14.22.24	41.94.15.12.24	41.94.15.22.24	41.94.16.12.24	41.94.16.22.24	41.94.19.12.24	41.94.19.22.24
	41.94.24.12.24	41.94.24.22.24	41.94.25.12.24	41.94.25.22.24	41.94.26.12.24	41.94.26.22.24	41.94.29.12.24	41.94.29.22.24
	41.94.34.12.24	41.94.34.22.24	41.94.35.12.24	41.94.35.22.24	41.94.36.12.24	41.94.36.22.24	41.94.39.12.24	41.94.39.22.24


Nomenclature - Illuminated Mushroom Head Pushbutton

Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Illuminated Mushroom Head Pushbutton - Square

Appearance	Operation	Lamp	Voltage	Contact	Red		Amber	
					IP40	IP65	IP40	IP65
 <p>Square Illuminated</p>	Momentary	LED	6V	1NO-1NC	41.85.12.11.06	41.85.12.21.06	41.85.13.11.06	41.85.13.21.06
				2NO-2NC	41.85.22.11.06	41.85.22.21.06	41.85.23.11.06	41.85.23.21.06
				3NO-3NC	41.85.32.11.06	41.85.32.21.06	41.85.33.11.06	41.85.33.21.06
			12V	1NO-1NC	41.85.12.11.12	41.85.12.21.12	41.85.13.11.12	41.85.13.21.12
				2NO-2NC	41.85.22.11.12	41.85.22.21.12	41.85.23.11.12	41.85.23.21.12
				3NO-3NC	41.85.32.11.12	41.85.32.21.12	41.85.33.11.12	41.85.33.21.12
		24V	1NO-1NC	41.85.12.11.24	41.85.12.21.24	41.85.13.11.24	41.85.13.21.24	
			2NO-2NC	41.85.22.11.24	41.85.22.21.24	41.85.23.11.24	41.85.23.21.24	
			3NO-3NC	41.85.32.11.24	41.85.32.21.24	41.85.33.11.24	41.85.33.21.24	
		Filament	6V	1NO-1NC	41.85.12.12.06	41.85.12.22.06	41.85.13.12.06	41.85.13.22.06
				2NO-2NC	41.85.22.12.06	41.85.22.22.06	41.85.23.12.06	41.85.23.22.06
				3NO-3NC	41.85.32.12.06	41.85.32.22.06	41.85.33.12.06	41.85.33.22.06
	12V		1NO-1NC	41.85.12.12.12	41.85.12.22.12	41.85.13.12.12	41.85.13.22.12	
			2NO-2NC	41.85.22.12.12	41.85.22.22.12	41.85.23.12.12	41.85.23.22.12	
			3NO-3NC	41.85.32.12.12	41.85.32.22.12	41.85.33.12.12	41.85.33.22.12	
	24V	1NO-1NC	41.85.12.12.24	41.85.12.22.24	41.85.13.12.24	41.85.13.22.24		
		2NO-2NC	41.85.22.12.24	41.85.22.22.24	41.85.23.12.24	41.85.23.22.24		
		3NO-3NC	41.85.32.12.24	41.85.32.22.24	41.85.33.12.24	41.85.33.22.24		
 <p>Square Illuminated</p>	Maintained	LED	6V	1NO-1NC	41.95.12.11.06	41.95.12.21.06	41.95.13.11.06	41.95.13.21.06
				2NO-2NC	41.95.22.11.06	41.95.22.21.06	41.95.23.11.06	41.95.23.21.06
				3NO-3NC	41.95.32.11.06	41.95.32.21.06	41.95.33.11.06	41.95.33.21.06
			12V	1NO-1NC	41.95.12.11.12	41.95.12.21.12	41.95.13.11.12	41.95.13.21.12
				2NO-2NC	41.95.22.11.12	41.95.22.21.12	41.95.23.11.12	41.95.23.21.12
				3NO-3NC	41.95.32.11.12	41.95.32.21.12	41.95.33.11.12	41.95.33.21.12
		24V	1NO-1NC	41.95.12.11.24	41.95.12.21.24	41.95.13.11.24	41.95.13.21.24	
			2NO-2NC	41.95.22.11.24	41.95.22.21.24	41.95.23.11.24	41.95.23.21.24	
			3NO-3NC	41.95.32.11.24	41.95.32.21.24	41.95.33.11.24	41.95.33.21.24	
		Filament	6V	1NO-1NC	41.95.12.12.06	41.95.12.22.06	41.95.13.12.06	41.95.13.22.06
				2NO-2NC	41.95.22.12.06	41.95.22.22.06	41.95.23.12.06	41.95.23.22.06
				3NO-3NC	41.95.32.12.06	41.95.32.22.06	41.95.33.12.06	41.95.33.22.06
	12V		1NO-1NC	41.95.12.12.12	41.95.12.22.12	41.95.13.12.12	41.95.13.22.12	
			2NO-2NC	41.95.22.12.12	41.95.22.22.12	41.95.23.12.12	41.95.23.22.12	
			3NO-3NC	41.95.32.12.12	41.95.32.22.12	41.95.33.12.12	41.95.33.22.12	
	24V	1NO-1NC	41.95.12.12.24	41.95.12.22.24	41.95.13.12.24	41.95.13.22.24		
		2NO-2NC	41.95.22.12.24	41.95.22.22.24	41.95.23.12.24	41.95.23.22.24		
		3NO-3NC	41.95.32.12.24	41.95.32.22.24	41.95.33.12.24	41.95.33.22.24		

Dimensions - Illuminated Mushroom Head Pushbutton



Refer to next page for more color selection.

Illuminated Mushroom Head Pushbutton - Square

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.85.14.11.06	41.85.14.21.06	41.85.15.11.06	41.85.15.21.06	41.85.16.11.06	41.85.16.21.06	41.85.19.11.06	41.85.19.21.06
	41.85.24.11.06	41.85.24.21.06	41.85.25.11.06	41.85.25.21.06	41.85.26.11.06	41.85.26.21.06	41.85.29.11.06	41.85.29.21.06
	41.85.34.11.06	41.85.34.21.06	41.85.35.11.06	41.85.35.21.06	41.85.36.11.06	41.85.36.21.06	41.85.39.11.06	41.85.39.21.06
	41.85.14.11.12	41.85.14.21.12	41.85.15.11.12	41.85.15.21.12	41.85.16.11.12	41.85.16.21.12	41.85.19.11.12	41.85.19.21.12
	41.85.24.11.12	41.85.24.21.12	41.85.25.11.12	41.85.25.21.12	41.85.26.11.12	41.85.26.21.12	41.85.29.11.12	41.85.29.21.12
	41.85.34.11.12	41.85.34.21.12	41.85.35.11.12	41.85.35.21.12	41.85.36.11.12	41.85.36.21.12	41.85.39.11.12	41.85.39.21.12
	41.85.14.11.24	41.85.14.21.24	41.85.15.11.24	41.85.15.21.24	41.85.16.11.24	41.85.16.21.24	41.85.19.11.24	41.85.19.21.24
	41.85.24.11.24	41.85.24.21.24	41.85.25.11.24	41.85.25.21.24	41.85.26.11.24	41.85.26.21.24	41.85.29.11.24	41.85.29.21.24
	41.85.34.11.24	41.85.34.21.24	41.85.35.11.24	41.85.35.21.24	41.85.36.11.24	41.85.36.21.24	41.85.39.11.24	41.85.39.21.24
	41.85.14.12.06	41.85.14.22.06	41.85.15.12.06	41.85.15.22.06	41.85.16.12.06	41.85.16.22.06	41.85.19.12.06	41.85.19.22.06
	41.85.24.12.06	41.85.24.22.06	41.85.25.12.06	41.85.25.22.06	41.85.26.12.06	41.85.26.22.06	41.85.29.12.06	41.85.29.22.06
	41.85.34.12.06	41.85.34.22.06	41.85.35.12.06	41.85.35.22.06	41.85.36.12.06	41.85.36.22.06	41.85.39.12.06	41.85.39.22.06
	41.85.14.12.12	41.85.14.22.12	41.85.15.12.12	41.85.15.22.12	41.85.16.12.12	41.85.16.22.12	41.85.19.12.12	41.85.19.22.12
	41.85.24.12.12	41.85.24.22.12	41.85.25.12.12	41.85.25.22.12	41.85.26.12.12	41.85.26.22.12	41.85.29.12.12	41.85.29.22.12
	41.85.34.12.12	41.85.34.22.12	41.85.35.12.12	41.85.35.22.12	41.85.36.12.12	41.85.36.22.12	41.85.39.12.12	41.85.39.22.12
	41.85.14.12.24	41.85.14.22.24	41.85.15.12.24	41.85.15.22.24	41.85.16.12.24	41.85.16.22.24	41.85.19.12.24	41.85.19.22.24
	41.85.24.12.24	41.85.24.22.24	41.85.25.12.24	41.85.25.22.24	41.85.26.12.24	41.85.26.22.24	41.85.29.12.24	41.85.29.22.24
	41.85.34.12.24	41.85.34.22.24	41.85.35.12.24	41.85.35.22.24	41.85.36.12.24	41.85.36.22.24	41.85.39.12.24	41.85.39.22.24
	41.95.14.11.06	41.95.14.21.06	41.95.15.11.06	41.95.15.21.06	41.95.16.11.06	41.95.16.21.06	41.95.19.11.06	41.95.19.21.06
	41.95.24.11.06	41.95.24.21.06	41.95.25.11.06	41.95.25.21.06	41.95.26.11.06	41.95.26.21.06	41.95.29.11.06	41.95.29.21.06
	41.95.34.11.06	41.95.34.21.06	41.95.35.11.06	41.95.35.21.06	41.95.36.11.06	41.95.36.21.06	41.95.39.11.06	41.95.39.21.06
	41.95.14.11.12	41.95.14.21.12	41.95.15.11.12	41.95.15.21.12	41.95.16.11.12	41.95.16.21.12	41.95.19.11.12	41.95.19.21.12
	41.95.24.11.12	41.95.24.21.12	41.95.25.11.12	41.95.25.21.12	41.95.26.11.12	41.95.26.21.12	41.95.29.11.12	41.95.29.21.12
	41.95.34.11.12	41.95.34.21.12	41.95.35.11.12	41.95.35.21.12	41.95.36.11.12	41.95.36.21.12	41.95.39.11.12	41.95.39.21.12
	41.95.14.11.24	41.95.14.21.24	41.95.15.11.24	41.95.15.21.24	41.95.16.11.24	41.95.16.21.24	41.95.19.11.24	41.95.19.21.24
	41.95.24.11.24	41.95.24.21.24	41.95.25.11.24	41.95.25.21.24	41.95.26.11.24	41.95.26.21.24	41.95.29.11.24	41.95.29.21.24
	41.95.34.11.24	41.95.34.21.24	41.95.35.11.24	41.95.35.21.24	41.95.36.11.24	41.95.36.21.24	41.95.39.11.24	41.95.39.21.24
	41.95.14.12.06	41.95.14.22.06	41.95.15.12.06	41.95.15.22.06	41.95.16.12.06	41.95.16.22.06	41.95.19.12.06	41.95.19.22.06
	41.95.24.12.06	41.95.24.22.06	41.95.25.12.06	41.95.25.22.06	41.95.26.12.06	41.95.26.22.06	41.95.29.12.06	41.95.29.22.06
	41.95.34.12.06	41.95.34.22.06	41.95.35.12.06	41.95.35.22.06	41.95.36.12.06	41.95.36.22.06	41.95.39.12.06	41.95.39.22.06
	41.95.14.12.12	41.95.14.22.12	41.95.15.12.12	41.95.15.22.12	41.95.16.12.12	41.95.16.22.12	41.95.19.12.12	41.95.19.22.12
	41.95.24.12.12	41.95.24.22.12	41.95.25.12.12	41.95.25.22.12	41.95.26.12.12	41.95.26.22.12	41.95.29.12.12	41.95.29.22.12
	41.95.34.12.12	41.95.34.22.12	41.95.35.12.12	41.95.35.22.12	41.95.36.12.12	41.95.36.22.12	41.95.39.12.12	41.95.39.22.12
	41.95.14.12.24	41.95.14.22.24	41.95.15.12.24	41.95.15.22.24	41.95.16.12.24	41.95.16.22.24	41.95.19.12.24	41.95.19.22.24
	41.95.24.12.24	41.95.24.22.24	41.95.25.12.24	41.95.25.22.24	41.95.26.12.24	41.95.26.22.24	41.95.29.12.24	41.95.29.22.24
	41.95.34.12.24	41.95.34.22.24	41.95.35.12.24	41.95.35.22.24	41.95.36.12.24	41.95.36.22.24	41.95.39.12.24	41.95.39.22.24


Nomenclature - Illuminated Mushroom Head Pushbutton

Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Illuminated Mushroom Head Pushbutton - Rectangular

Appearance	Operation	Lamp	Voltage	Contact	Red		Amber		
					IP40	IP65	IP40	IP65	
 Rectangle Illuminated	Momentary	LED	6V	1NO-1NC	41.86.12.11.06	41.86.12.21.06	41.86.13.11.06	41.86.13.21.06	
				2NO-2NC	41.86.22.11.06	41.86.22.21.06	41.86.23.11.06	41.86.23.21.06	
				3NO-3NC	41.86.32.11.06	41.86.32.21.06	41.86.33.11.06	41.86.33.21.06	
			12V	1NO-1NC	41.86.12.11.12	41.86.12.21.12	41.86.13.11.12	41.86.13.21.12	
				2NO-2NC	41.86.22.11.12	41.86.22.21.12	41.86.23.11.12	41.86.23.21.12	
				3NO-3NC	41.86.32.11.12	41.86.32.21.12	41.86.33.11.12	41.86.33.21.12	
		24V	1NO-1NC	41.86.12.11.24	41.86.12.21.24	41.86.13.11.24	41.86.13.21.24		
			2NO-2NC	41.86.22.11.24	41.86.22.21.24	41.86.23.11.24	41.86.23.21.24		
			3NO-3NC	41.86.32.11.24	41.86.32.21.24	41.86.33.11.24	41.86.33.21.24		
		Filament	6V	1NO-1NC	41.86.12.12.06	41.86.12.22.06	41.86.13.12.06	41.86.13.22.06	
				2NO-2NC	41.86.22.12.06	41.86.22.22.06	41.86.23.12.06	41.86.23.22.06	
				3NO-3NC	41.86.32.12.06	41.86.32.22.06	41.86.33.12.06	41.86.33.22.06	
	12V		1NO-1NC	41.86.12.12.12	41.86.12.22.12	41.86.13.12.12	41.86.13.22.12		
			2NO-2NC	41.86.22.12.12	41.86.22.22.12	41.86.23.12.12	41.86.23.22.12		
			3NO-3NC	41.86.32.12.12	41.86.32.22.12	41.86.33.12.12	41.86.33.22.12		
	24V	1NO-1NC	41.86.12.12.24	41.86.12.22.24	41.86.13.12.24	41.86.13.22.24			
		2NO-2NC	41.86.22.12.24	41.86.22.22.24	41.86.23.12.24	41.86.23.22.24			
		3NO-3NC	41.86.32.12.24	41.86.32.22.24	41.86.33.12.24	41.86.33.22.24			
 Rectangle Illuminated	Maintained	LED	6V	1NO-1NC	41.96.12.11.06	41.96.12.21.06	41.96.13.11.06	41.96.13.21.06	
				2NO-2NC	41.96.22.11.06	41.96.22.21.06	41.96.23.11.06	41.96.23.21.06	
				3NO-3NC	41.96.32.11.06	41.96.32.21.06	41.96.33.11.06	41.96.33.21.06	
			12V	1NO-1NC	41.96.12.11.12	41.96.12.21.12	41.96.13.11.12	41.96.13.21.12	
				2NO-2NC	41.96.22.11.12	41.96.22.21.12	41.96.23.11.12	41.96.23.21.12	
				3NO-3NC	41.96.32.11.12	41.96.32.21.12	41.96.33.11.12	41.96.33.21.12	
		24V	1NO-1NC	41.96.12.11.24	41.96.12.21.24	41.96.13.11.24	41.96.13.21.24		
			2NO-2NC	41.96.22.11.24	41.96.22.21.24	41.96.23.11.24	41.96.23.21.24		
			3NO-3NC	41.96.32.11.24	41.96.32.21.24	41.96.33.11.24	41.96.33.21.24		
		Filament	6V	1NO-1NC	41.96.12.12.06	41.96.12.22.06	41.96.13.12.06	41.96.13.22.06	
				2NO-2NC	41.96.22.12.06	41.96.22.22.06	41.96.23.12.06	41.96.23.22.06	
				3NO-3NC	41.96.32.12.06	41.96.32.22.06	41.96.33.12.06	41.96.33.22.06	
	12V		1NO-1NC	41.96.12.12.12	41.96.12.22.12	41.96.13.12.12	41.96.13.22.12		
			2NO-2NC	41.96.22.12.12	41.96.22.22.12	41.96.23.12.12	41.96.23.22.12		
			3NO-3NC	41.96.32.12.12	41.96.32.22.12	41.96.33.12.12	41.96.33.22.12		
	24V	1NO-1NC	41.96.12.12.24	41.96.12.22.24	41.96.13.12.24	41.96.13.22.24			
		2NO-2NC	41.96.22.12.24	41.96.22.22.24	41.96.23.12.24	41.96.23.22.24			
		3NO-3NC	41.96.32.12.24	41.96.32.22.24	41.96.33.12.24	41.96.33.22.24			

Dimensions - Illuminated Mushroom Head Pushbutton



Refer to next page for more color selection.

Illuminated Mushroom Head Pushbutton - Rectangular

	Yellow		Green		Blue		White	
	IP40	IP65	IP40	IP65	IP40	IP65	IP40	IP65
	41.86.14.11.06	41.86.14.21.06	41.86.15.11.06	41.86.15.21.06	41.86.16.11.06	41.86.16.21.06	41.86.19.11.06	41.86.19.21.06
	41.86.24.11.06	41.86.24.21.06	41.86.25.11.06	41.86.25.21.06	41.86.26.11.06	41.86.26.21.06	41.86.29.11.06	41.86.29.21.06
	41.86.34.11.06	41.86.34.21.06	41.86.35.11.06	41.86.35.21.06	41.86.36.11.06	41.86.36.21.06	41.86.39.11.06	41.86.39.21.06
	41.86.14.11.12	41.86.14.21.12	41.86.15.11.12	41.86.15.21.12	41.86.16.11.12	41.86.16.21.12	41.86.19.11.12	41.86.19.21.12
	41.86.24.11.12	41.86.24.21.12	41.86.25.11.12	41.86.25.21.12	41.86.26.11.12	41.86.26.21.12	41.86.29.11.12	41.86.29.21.12
	41.86.34.11.12	41.86.34.21.12	41.86.35.11.12	41.86.35.21.12	41.86.36.11.12	41.86.36.21.12	41.86.39.11.12	41.86.39.21.12
	41.86.14.11.24	41.86.14.21.24	41.86.15.11.24	41.86.15.21.24	41.86.16.11.24	41.86.16.21.24	41.86.19.11.24	41.86.19.21.24
	41.86.24.11.24	41.86.24.21.24	41.86.25.11.24	41.86.25.21.24	41.86.26.11.24	41.86.26.21.24	41.86.29.11.24	41.86.29.21.24
	41.86.34.11.24	41.86.34.21.24	41.86.35.11.24	41.86.35.21.24	41.86.36.11.24	41.86.36.21.24	41.86.39.11.24	41.86.39.21.24
	41.86.14.12.06	41.86.14.22.06	41.86.15.12.06	41.86.15.22.06	41.86.16.12.06	41.86.16.22.06	41.86.19.12.06	41.86.19.22.06
	41.86.24.12.06	41.86.24.22.06	41.86.25.12.06	41.86.25.22.06	41.86.26.12.06	41.86.26.22.06	41.86.29.12.06	41.86.29.22.06
	41.86.34.12.06	41.86.34.22.06	41.86.35.12.06	41.86.35.22.06	41.86.36.12.06	41.86.36.22.06	41.86.39.12.06	41.86.39.22.06
	41.86.14.12.12	41.86.14.22.12	41.86.15.12.12	41.86.15.22.12	41.86.16.12.12	41.86.16.22.12	41.86.19.12.12	41.86.19.22.12
	41.86.24.12.12	41.86.24.22.12	41.86.25.12.12	41.86.25.22.12	41.86.26.12.12	41.86.26.22.12	41.86.29.12.12	41.86.29.22.12
	41.86.34.12.12	41.86.34.22.12	41.86.35.12.12	41.86.35.22.12	41.86.36.12.12	41.86.36.22.12	41.86.39.12.12	41.86.39.22.12
	41.86.14.12.24	41.86.14.22.24	41.86.15.12.24	41.86.15.22.24	41.86.16.12.24	41.86.16.22.24	41.86.19.12.24	41.86.19.22.24
	41.86.24.12.24	41.86.24.22.24	41.86.25.12.24	41.86.25.22.24	41.86.26.12.24	41.86.26.22.24	41.86.29.12.24	41.86.29.22.24
	41.86.34.12.24	41.86.34.22.24	41.86.35.12.24	41.86.35.22.24	41.86.36.12.24	41.86.36.22.24	41.86.39.12.24	41.86.39.22.24
	41.96.14.11.06	41.96.14.21.06	41.96.15.11.06	41.96.15.21.06	41.96.16.11.06	41.96.16.21.06	41.96.19.11.06	41.96.19.21.06
	41.96.24.11.06	41.96.24.21.06	41.96.25.11.06	41.96.25.21.06	41.96.26.11.06	41.96.26.21.06	41.96.29.11.06	41.96.29.21.06
	41.96.34.11.06	41.96.34.21.06	41.96.35.11.06	41.96.35.21.06	41.96.36.11.06	41.96.36.21.06	41.96.39.11.06	41.96.39.21.06
	41.96.14.11.12	41.96.14.21.12	41.96.15.11.12	41.96.15.21.12	41.96.16.11.12	41.96.16.21.12	41.96.19.11.12	41.96.19.21.12
	41.96.24.11.12	41.96.24.21.12	41.96.25.11.12	41.96.25.21.12	41.96.26.11.12	41.96.26.21.12	41.96.29.11.12	41.96.29.21.12
	41.96.34.11.12	41.96.34.21.12	41.96.35.11.12	41.96.35.21.12	41.96.36.11.12	41.96.36.21.12	41.96.39.11.12	41.96.39.21.12
	41.96.14.11.24	41.96.14.21.24	41.96.15.11.24	41.96.15.21.24	41.96.16.11.24	41.96.16.21.24	41.96.19.11.24	41.96.19.21.24
	41.96.24.11.24	41.96.24.21.24	41.96.25.11.24	41.96.25.21.24	41.96.26.11.24	41.96.26.21.24	41.96.29.11.24	41.96.29.21.24
	41.96.34.11.24	41.96.34.21.24	41.96.35.11.24	41.96.35.21.24	41.96.36.11.24	41.96.36.21.24	41.96.39.11.24	41.96.39.21.24
	41.96.14.12.06	41.96.14.22.06	41.96.15.12.06	41.96.15.22.06	41.96.16.12.06	41.96.16.22.06	41.96.19.12.06	41.96.19.22.06
	41.96.24.12.06	41.96.24.22.06	41.96.25.12.06	41.96.25.22.06	41.96.26.12.06	41.96.26.22.06	41.96.29.12.06	41.96.29.22.06
	41.96.34.12.06	41.96.34.22.06	41.96.35.12.06	41.96.35.22.06	41.96.36.12.06	41.96.36.22.06	41.96.39.12.06	41.96.39.22.06
	41.96.14.12.12	41.96.14.22.12	41.96.15.12.12	41.96.15.22.12	41.96.16.12.12	41.96.16.22.12	41.96.19.12.12	41.96.19.22.12
	41.96.24.12.12	41.96.24.22.12	41.96.25.12.12	41.96.25.22.12	41.96.26.12.12	41.96.26.22.12	41.96.29.12.12	41.96.29.22.12
	41.96.34.12.12	41.96.34.22.12	41.96.35.12.12	41.96.35.22.12	41.96.36.12.12	41.96.36.22.12	41.96.39.12.12	41.96.39.22.12
	41.96.14.12.24	41.96.14.22.24	41.96.15.12.24	41.96.15.22.24	41.96.16.12.24	41.96.16.22.24	41.96.19.12.24	41.96.19.22.24
	41.96.24.12.24	41.96.24.22.24	41.96.25.12.24	41.96.25.22.24	41.96.26.12.24	41.96.26.22.24	41.96.29.12.24	41.96.29.22.24
	41.96.34.12.24	41.96.34.22.24	41.96.35.12.24	41.96.35.22.24	41.96.36.12.24	41.96.36.22.24	41.96.39.12.24	41.96.39.22.24

Nomenclature - Illuminated Mushroom Head Pushbutton

Ordering	Description	Sample
2	Red	
3	Amber	
4	Yellow	
5	Green	
6	Blue	
9	White	

Dimensions

Round	Square	Rectangular
<p>Pushbuttons</p>	<p>Pushbuttons</p>	<p>Pushbuttons</p>
<p>Key Selector Switches</p>	<p>Key Selector Switches</p>	<p>Key Selector Switches</p>

All dimension are in mm.

Selector Switch Contact Arrangement

Positions		1NO-1NC		2NO-2NC		3NO-3NC	
90° 2 Positions	Left ↺	U	—	U	1 ○ ○ 2 3 ○ ○ 4	U	1 ○ ○ 2 3 ○ ○ 4
		M	1 ○ ○ 2 3 ○ ○ 4	M	—	M	1 ○ ○ 2 3 ○ ○ 4
		L	—	L	1 ○ ○ 2 3 ○ ○ 4	L	1 ○ ○ 2 3 ○ ○ 4
	Right ↻	U	—	U	1 ○ ○ 2 3 ○ — ○ 4	U	1 ○ ○ 2 3 ○ — ○ 4
		M	1 ○ ○ 2 3 ○ — ○ 4	M	—	M	1 ○ ○ 2 3 ○ — ○ 4
		L	—	L	1 ○ ○ 2 3 ○ — ○ 4	L	1 ○ ○ 2 3 ○ — ○ 4
45° 3 Positions	Left ↺	U	—	U	1 ○ ○ 2 3 ○ ○ 4	U	1 ○ ○ 2 3 ○ ○ 4
		M	—	M	—	M	1 ○ ○ 2 3 ○ — ○ 4
		L	—	L	1 ○ ○ 2 3 ○ — ○ 4	L	1 ○ ○ 2 3 ○ — ○ 4
	Center ⊕	U	—	U	1 ○ ○ 2 3 ○ ○ 4	U	1 ○ ○ 2 3 ○ ○ 4
		M	—	M	—	M	1 ○ ○ 2 3 ○ ○ 4
		L	—	L	1 ○ ○ 2 3 ○ ○ 4	L	1 ○ ○ 2 3 ○ ○ 4
	Right ↻	U	—	U	1 ○ ○ 2 3 ○ — ○ 4	U	1 ○ ○ 2 3 ○ — ○ 4
		M	—	M	—	M	1 ○ ○ 2 3 ○ — ○ 4
		L	—	L	1 ○ ○ 2 3 ○ ○ 4	L	1 ○ ○ 2 3 ○ ○ 4

U: Upper Contact Blocks
M: Middle Contact Blocks
L: Lower Contact Blocks


Note:

- Turn off the power to the 41 series control units before starting installation to prevent fire hazard.


Emergency Stop

Appearance	Operation Type	Contact	Color	Model No.	
				IP40	IP65
 Round	Pushlock Turn Reset	1NO-1NC	Red	41.08.12.10	41.08.12.20
	Pushlock Turn Reset	2NO-2NC	Red	41.08.22.10	41.08.22.20
	Pushlock Turn Reset	3NO-3NC	Red	41.08.32.10	41.08.32.20

Dimensions - Emergency Stop



Mounting Space



Safety Precautions

Pushbutton Replacement

Make sure pushbuttons are not locked, In the case of illuminated or Non Illuminated pushbutton switches. This could result in malfunctioning the pushbuttons.

Contact block

Deformation or damage may occur If excessive force is applied when attempting to open the support legs for the contact block holder.

Handling

Do not apply torque in excess of 1.0 N.m to operate the selectors switches. Required operating force of switches is less than 0.1 N.m.

Make sure to operate the pushbuttons by hand. Do not tap on a pushbuttons to turn it Off and On, this may result is malfunctioning and damage.

Operation

Do not use a hitting or bouncing action to operate the button that may result in breakage of the lens.



Terms And Conditions

Please read this catalog before purchasing any products. Please consult your *WERNER* representative for any clarifications or comments.

Application Considerations

WERNER shall not be responsible for conformity with any regulations, codes or standards that apply to use of the products. *WERNER* shall provide applicable third party certification documents identifying ratings and limitations of use that apply to the products in case of the customer's request.

Prevent use the products for an application involving risk to life or property. Be sure that the *WERNER*'s products are properly rated and installed for the overall system or equipment.

WERNER shall not be responsible for the user's programming of a programmable products.

Warranty

WERNER's warranty represents that the products are free from defects in materials and workmanship for a period of one year.

WERNER shall not be responsible for any special loss of profit, commercial loss, indirect or consequential damages relevant to products.

WERNER shall not be responsible for repair, warranty or any claims regarding the products unless *WERNER*'s Analysis confirm that the products were properly stored, installed, handled, maintained and not a result of accident, insufficient, abuse, misuse, natural disaster, improper installation excessive electrical supply, environmental conditions or abnormal mechanical.

Disclaimers

WERNER shall practice to change type/model numbers when published ratings or features are changed, however some specifications of the products may be changed without any notice.

When in doubt, please consult with your *WERNER* representative to confirm actual specifications of products.

WERNER shall change product specifications and accessories at any time based on improvements and other reasons.

The information in this catalog has been carefully checked. However, *WERNER* take no responsibilities for clerical, typographical or proofreading errors.



Living Industrial Partnerships



Werner Electric GmbH

Otto-Brenner-Str. 209
D-33604 Bielefeld
Germany
T: +49 521 9276307
F: +49 521 9276102
E: info@wernerelectric.de
W: www.wernerelectric.de

WE Electric India (P) Ltd.

#278-B, Hootagalli,
Hebbal Industrial area
Mysore-570018, India
T: +91 821-425 4500
F: +91 821-425 4599
E: info@in.wernerelectric.de
W: www.wernerelectric.de